
PEtab

Release latest

Mar 18, 2020

1	Format version: 1	1
2	Purpose	3
3	Overview	5
4	SBML model definition	7
5	Condition table	9
5.1	Detailed field description	9
6	Measurement table	11
6.1	Detailed field description	11
7	Observables table	13
7.1	Detailed field description:	13
8	Parameter table	15
8.1	Detailed field description:	15
9	Visualization table	19
9.1	Detailed field description:	19
9.2	Extensions	20
9.3	Examples	20
10	YAML file for grouping files	21
10.1	Parameter estimation problems combining multiple models	21
11	API Reference	23
11.1	petab	23
11.2	petab.composite_problem	24
11.3	petab.core	24
11.4	petab.conditions	27
11.5	petab.C	27
11.6	petab.lint	28
11.7	petab.measurements	33
11.8	petab.parameter_mapping	35
11.9	petab.parameters	41

11.10	petab.problem	44
11.11	petab.sampling	49
11.12	petab.sbml	50
11.13	petab.yaml	53
11.14	petab.visualize.data_overview	55
11.15	petab.visualize.helper_functions	56
11.16	petab.visualize.plot_data_and_simulation	61
11.17	petab.visualize.plotting_config	62
12	PEtab changelog	63
12.1	0.1 series	63
12.1.1	0.1.5	63
12.1.2	0.1.4	63
12.1.3	0.1.3	64
12.1.4	0.1.2	64
12.1.5	0.1.1	65
12.1.6	0.1.0	65
12.1.7	0.0.2	65
12.1.8	0.0.1	66
12.2	0.0 series	66
12.2.1	0.0.0a17	66
12.2.2	0.0.0a16 and earlier	66
13	License	67
14	PEtab logo license	69
15	Examples	71
15.1	Using petablint	71
15.2	Visualization of data and simulations	72
16	Indices and tables	79
	Python Module Index	81
	Index	83

CHAPTER 1

Format version: 1

This document explains the PEtab data format.

CHAPTER 2

Purpose

Providing a standardized way for specifying parameter estimation problems in systems biology, especially for the case of Ordinary Differential Equation (ODE) models.

The P_Etab data format specifies a parameter estimation problem using a number of text-based files (Systems Biology Markup Language (SBML) and Tab-Separated Values (TSV)), i.e.

- An SBML model [SBML]
- A measurement file to fit the model to [TSV]
- A condition file specifying model inputs and condition-specific parameters [TSV]
- An observable file specifying the observation model [TSV]
- A parameter file specifying optimization parameters and related information [TSV]
- (optional) A simulation file, which has the same format as the measurement file, but contains model simulations [TSV]
- (optional) A visualization file, which contains specifications how the data and/or simulations should be plotted by the visualization routines [TSV]


PEtab problem

Model



➤ Reaction network

Observables



➤ Observables
➤ Noise model

Conditions Parameters

constituting a PEPab problem

The following sections will describe the minimum requirements of those components in the core standard, which should provide all information for defining the parameter estimation problem.

Extensions of this format (e.g. additional columns in the measurement table) are possible and intended. However, while those columns may provide extra information for example for plotting, downstream analysis, or for more efficient parameter estimation, they should not affect the optimization problem as such.

General remarks

- All model entities, column names and row names are case-sensitive
- All identifiers must consist only of upper and lower case letters, digits and underscores, and must not start with a digit.
- Fields in “[]” are optional and may be left empty.

CHAPTER 4

SBML model definition

The model must be specified as valid SBML. There are no further restrictions.

Condition table

The condition table specifies parameters, or initial values of species and compartments for specific simulation conditions (generally corresponding to different experimental conditions).

This is specified as a tab-separated value file in the following way:

Row- and column-ordering are arbitrary, although specifying `conditionId` first may improve human readability.

Additional columns are *not* allowed.

5.1 Detailed field description

- `conditionId` [STRING, NOT NULL]

Unique identifier for the simulation/experimental condition, to be referenced by the measurement table described below.

- `conditionName` [STRING, OPTIONAL]

Condition names are arbitrary strings to describe the given condition. They may be used for reporting or visualization.

- `${parameterOrSpeciesOrCompartmentId1}`

Further columns may be global parameter IDs, IDs of species or compartments as defined in the SBML model. Only one column is allowed per ID. Values for these condition parameters may be provided either as numeric values, or as IDs defined in the SBML model, the parameter table or both.

- `${parameterId}`

The values will override any parameter values specified in the model.

- `${speciesId}`

If a species ID is provided, it is interpreted as the initial concentration/amount of that species and will override the initial concentration/amount given in the SBML model or given by a preequilibration condition. If NaN is provided for a condition, the result of the preequilibration (or initial concentration/amount from the SBML model, if no preequilibration is defined) is used.

– `${compartmentId}`

If a compartment ID is provided, it is interpreted as the initial compartment size.

Measurement table

A tab-separated values files containing all measurements to be used for model training or validation.

Expected to have the following named columns in any (but preferably this) order:

(wrapped for readability)

Additional (non-standard) columns may be added. If the additional plotting functionality of PETab should be used, such columns could be

where `datasetId` is a necessary column to use particular plotting functionality, and `replicateId` is optional, which can be used to group replicates and plot error bars.

6.1 Detailed field description

- `observableId` [STRING, NOT NULL, REFERENCES(observables.observableID)]
Observable ID as defined in the observables table described below.
- `preequilibrationConditionId` [STRING OR NULL, REFERENCES(conditionsTable.conditionID), OPTIONAL]
The `conditionId` to be used for preequilibration. E.g. for drug treatments, the model would be preequilibrated with the no-drug condition. Empty for no preequilibration.
- `simulationConditionId` [STRING, NOT NULL, REFERENCES(conditionsTable.conditionID)]
`conditionId` as provided in the condition table, specifying the condition-specific parameters used for simulation.
- `measurement` [NUMERIC, NOT NULL]
The measured value in the same units/scale as the model output.
- `time` [NUMERIC OR STRING, NOT NULL]
Time point of the measurement in the time unit specified in the SBML model, numeric value or `inf` (lower-case) for steady-state measurements.

- `observableParameters` [NUMERIC, STRING OR NULL, OPTIONAL]

This field allows overriding or introducing condition-specific versions of output parameters defined in the observation model. The model can define observables (see below) containing place-holder parameters which can be replaced by condition-specific dynamic or constant parameters. Placeholder parameters must be named `observableParameter${n}_${observableId}` with `n` ranging from 1 (not 0) to the number of placeholders for the given observable, without gaps. If the observable specified under `observableId` contains no placeholders, this field must be empty. If it contains `n > 0` placeholders, this field must hold `n` semicolon-separated numeric values or parameter names. No trailing semicolon must be added.

Different lines for the same `observableId` may specify different parameters. This may be used to account for condition-specific or batch-specific parameters. This will translate into an extended optimization parameter vector.

All placeholders defined in the observation model must be overwritten here. If there are no placeholders used, this column may be omitted.

- `noiseParameters` [NUMERIC, STRING OR NULL, OPTIONAL]

The measurement standard deviation or NaN if the corresponding sigma is a model parameter.

Numeric values or parameter names are allowed. Same rules apply as for `observableParameters` in the previous point.

- `datasetId` [STRING, OPTIONAL]

The `datasetId` is used to group certain measurements to datasets. This is typically the case for data points which belong to the same observable, the same simulation and preequilibration condition, the same noise model, the same observable transformation and the same observable parameters. This grouping makes it possible to use the plotting routines which are provided in the PEtAb repository.

- `replicateId` [STRING, OPTIONAL]

The `replicateId` can be used to discern replicates with the same `datasetId`, which is helpful for plotting e.g. error bars.

Observables table

Parameter estimation requires linking experimental observations to the model of interest. Therefore, one needs to define observables (model outputs) and respective noise models, which represent the measurement process. Since parameter estimation is beyond the scope of SBML, there exists no standard way to specify observables (model outputs) and respective noise models. Therefore, in PETab observables are specified in a separate table as described in the following. This allows for a clear separation of the observation model and the underlying dynamic model, which allows, in most cases, to reuse any existing SBML model without modifications.

The observable table has the following columns:

7.1 Detailed field description:

- `observableId` [STRING]
Any identifier which would be a valid identifier in SBML. This is referenced by the `observableId` column in the measurement table. Must be different from any existing model entity or parameter introduced elsewhere.
- `[observableName]` [STRING, OPTIONAL]
Name of the observable. Only used for output, not for identification.
- `observableFormula` [STRING]
Observation function as plain text formula expression. May contain any symbol defined in the SBML model or parameter table. In the simplest case just an SBML species ID or an `AssignmentRule` target.
May introduce new parameters of the form `observableParameter${n}`, which are overridden by `observableParameters` in the measurement table (see description there).
- `observableTransformation` [STRING, OPTIONAL]
Transformation of the observable and measurement for computing the objective function. Must be one of `lin`, `log` or `log10`. Defaults to `lin`. The measurements and model outputs are both assumed to be provided in linear space.

- `noiseFormula` [NUMERICSTRING]

Measurement noise can be specified as a numerical value which will default to a Gaussian noise model if not specified differently in `noiseDistribution` with standard deviation as provided here. In this case, the same standard deviation is assumed for all measurements for the given observable.

Alternatively, some formula expression can be provided to specify more complex noise models. A noise model which accounts for relative and absolute contributions could, e.g., be defined as

$$\text{noiseParameter1_pErk} + \text{noiseParameter2_pErk} * \text{pErk}$$

with `noiseParameter1_pErk` denoting the absolute and `noiseParameter2_pErk` the relative contribution for the observable `pErk`. IDs of noise parameters that need to have different values for different measurements have the structure: `noiseParameter${indexOfNoiseParameter}_${observableId}` to facilitate automatic recognition. The specific values or parameters are assigned in the `noiseParameters` field of the *measurement table* (see above). Any parameters named `noiseParameter${1..n}` *must* be overwritten in the measurement table.

- `noiseDistribution` [STRING: ‘normal’ or ‘laplace’, OPTIONAL]

Assumed noise distribution for the given measurement. Only normally or Laplace distributed noise is currently allowed (log-normal and log-laplace are obtained by setting `observableTransformation` to `log`). Defaults to `normal`. If `normal`, the specified `noiseParameters` will be interpreted as standard deviation (*not* variance).

Parameter table

A tab-separated value text file containing information on model parameters.

This table *must* include the following parameters:

- Named parameter overrides introduced in the *conditions table*, unless defined in the SBML model
- Named parameter overrides introduced in the *measurement table*

and *must not* include:

- Placeholder parameters (see `observableParameters` and `noiseParameters` above)
- Parameters included as column names in the *condition table*
- Parameters that are `AssignmentRule` targets in the SBML model

it *may* include:

- Any SBML model parameter that was not excluded above
- Named parameter overrides introduced in the *conditions table*

One row per parameter with arbitrary order of rows and columns:

Additional columns may be added.

8.1 Detailed field description:

- `parameterId` [STRING, NOT NULL]

The `parameterId` of the parameter described in this row. This has to match the ID of a parameter specified in the SBML model, a parameter introduced as override in the condition table, or a parameter occurring in the `observableParameters` or `noiseParameters` column of the measurement table (see above).

- `parameterName` [STRING, OPTIONAL]

Parameter name to be used e.g. for plotting etc. Can be chosen freely. May or may not coincide with the SBML parameter name.

- `parameterScale` [lin|log|log10]
Scale of the parameter to be used during parameter estimation.
- `lowerBound` [NUMERIC]
Lower bound of the parameter used for optimization. Optional, if `estimate==0`. Must be provided in linear space, independent of `parameterScale`.
- `upperBound` [NUMERIC]
Upper bound of the parameter used for optimization. Optional, if `estimate==0`. Must be provided in linear space, independent of `parameterScale`.
- `nominalValue` [NUMERIC]
Some parameter value to be used if the parameter is not subject to estimation (see `estimate` below). Must be provided in linear space, independent of `parameterScale`. Optional, unless `estimate==0`.
- `estimate` [BOOL 0|1]
1 or 0, depending on, if the parameter is estimated (1) or set to a fixed value(0) (see `nominalValue`).
- `initializationPriorType` [STRING, OPTIONAL]
Prior types used for sampling of initial points for optimization. Sampled points are clipped to lie inside the parameter boundaries specified by `lowerBound` and `upperBound`. Defaults to `parameterScaleUniform`.
Possible prior types are:
 - *uniform*: flat prior on linear parameters
 - *normal*: Gaussian prior on linear parameters
 - *laplace*: Laplace prior on linear parameters
 - *logNormal*: exponentiated Gaussian prior on linear parameters
 - *logLaplace*: exponentiated Laplace prior on linear parameters
 - *parameterScaleUniform* (default): Flat prior on original parameter scale (equivalent to “no prior”)
 - *parameterScaleNormal*: Gaussian prior on original parameter scale
 - *parameterScaleLaplace*: Laplace prior on original parameter scale
- `initializationPriorParameters` [STRING, OPTIONAL]
Prior parameters used for sampling of initial points for optimization, separated by a semicolon. Defaults to `lowerBound;upperBound`.
So far, only numeric values will be supported, no parameter names. Parameters for the different prior types are:
 - *uniform*: lower bound; upper bound
 - *normal*: mean; standard deviation (**not** variance)
 - *laplace*: location; scale
 - *logNormal*: parameters of corresp. normal distribution (see: *normal*)
 - *logLaplace*: parameters of corresp. Laplace distribution (see: *laplace*)
 - *parameterScaleUniform*: lower bound; upper bound
 - *parameterScaleNormal*: mean; standard deviation (**not** variance)
 - *parameterScaleLaplace*: location; scale

- `objectivePriorType` [STRING, OPTIONAL]

Prior types used for the objective function during optimization or sampling. For possible values, see `initializationPriorType`.

- `objectivePriorParameters` [STRING, OPTIONAL]

Prior parameters used for the objective function during optimization. For more detailed documentation, see `initializationPriorParameters`.

Visualization table

A tab-separated value file containing the specification of the visualization routines which come with the PETA repository. Plots are in general collections of different datasets as specified using their `datasetId` (if provided) inside the measurement table.

Expected to have the following columns in any (but preferably this) order:

(wrapped for readability)

(wrapped for readability)

9.1 Detailed field description:

- `plotId` [STRING, NOT NULL]
An ID which corresponds to a specific plot. All datasets with the same `plotId` will be plotted into the same axes object.
- `plotName` [STRING, OPTIONAL]
A name for the specific plot.
- `plotTypeSimulation` [STRING, OPTIONAL]
The type of the corresponding plot, can be `LinePlot`, `BarPlot` and `ScatterPlot`. Default is `LinePlot`.
- `plotTypeData` [STRING, OPTIONAL]
The type how replicates should be handled, can be `MeanAndSD`, `MeanAndSEM`, `replicate` (for plotting all replicates separately), or `provided` (if numeric values for the noise level are provided in the measurement table). Default is `MeanAndSD`.
- `datasetId` [STRING, NOT NULL, REFERENCES(measurementTable.datasetId), OPTIONAL]
The datasets which should be grouped into one plot.

- `xValues` [STRING, OPTIONAL]

The independent variable, which will be plotted on the x-axis. Can be `time` (default, for time resolved data), or it can be `parameterOrStateId` for dose-response plots. The corresponding numeric values will be shown on the x-axis.

- `xOffset` [NUMERIC, OPTIONAL]

Possible data-offsets for the independent variable (default is 0).

- `xLabel` [STRING, OPTIONAL]

Label for the x-axis. Defaults to the entry in `xValues`.

- `xScale` [STRING, OPTIONAL]

Scale of the independent variable, can be `lin`, `log`, `log10` or `order`. The `order` value should be used if values of the independent variable are ordinal. This value can only be used in combination with `LinePlot` value for the `plotTypeSimulation` column. In this case, points on x axis will be placed equidistantly from each other.

- `yValues` [observableId, REFERENCES(measurementTable.observableId), OPTIONAL]

The observable which should be plotted on the y-axis.

- `yOffset` [NUMERIC, OPTIONAL]

Possible data-offsets for the observable (default is 0).

- `yLabel` [STRING, OPTIONAL]

Label for the y-axis. Defaults to the entry in `yValues`.

- `yScale` [STRING, OPTIONAL]

Scale of the observable, can be `lin`, `log`, or `log10`. Default is `lin`.

- `legendEntry` [STRING, OPTIONAL]

The name that should be displayed for the corresponding dataset in the legend and which defaults to the value in `datasetId`.

9.2 Extensions

Additional columns, such as `Color`, etc. may be specified.

9.3 Examples

Examples of the visualization table can be found in the [Benchmark model collection](#). For example, for [Chen_MSB2009](#) model.

YAML file for grouping files

To link the SBML model, measurement table, condition table, etc. in an unambiguous way, we use a [YAML](#) file.

This file also allows specifying a P_Etab version (as the format is not unlikely to change in the future).

Furthermore, this can be used to describe parameter estimation problems comprising multiple models (more details below).

The format is described in the schema [../petab/petab_schema.yaml](#), which allows for easy validation.

10.1 Parameter estimation problems combining multiple models

Parameter estimation problems can comprise multiple models. For now, P_Etab allows to specify multiple SBML models with corresponding condition and measurement tables, and one joint parameter table. This means that the parameter namespace is global. Therefore, parameters with the same ID in different models will be considered identical.

<code>petab</code>	PETab global
<code>petab.composite_problem</code>	PETab problems consisting of multiple models
<code>petab.core</code>	PETab core functions (or functions that don't fit anywhere else)
<code>petab.conditions</code>	Functions operating on the PETab condition table
<code>petab.C</code>	This file contains constant definitions.
<code>petab.lint</code>	Integrity checks and tests for specific features used
<code>petab.measurements</code>	Functions operating on the PETab measurement table
<code>petab.parameter_mapping</code>	Functions related to mapping parameter from model to parameter estimation problem
<code>petab.parameters</code>	Functions operating on the PETab parameter table
<code>petab.problem</code>	PETab Problem class
<code>petab.sampling</code>	Functions related to parameter sampling
<code>petab.sbml</code>	Functions for interacting with SBML models
<code>petab.yaml</code>	Code regarding the PETab YAML config files
<code>petab.visualize.data_overview</code>	Functions for creating an overview report of a PETab problem
<code>petab.visualize.helper_functions</code>	This file should contain the functions, which PETab internally needs for plotting, but which are not meant to be used by non-developers and should hence not be directly visible/usable when using <code>import petab.visualize</code> .
<code>petab.visualize.plot_data_and_simulation(...)</code>	Main function for plotting data and simulations.
<code>petab.visualize.plotting_config</code>	Plotting config

11.1 petab

PETab global

`petab.ENV_NUM_THREADS`

Name of environment variable to set number of threads or processes PETab should use for operations that can be performed in parallel. By default, all operations are performed sequentially.

11.2 petab.composite_problem

PETab problems consisting of multiple models

Classes

<code>CompositeProblem</code> (parameter_df, problems)	Representation of a PETab problem consisting of multiple models
--	---

```
class petab.composite_problem.CompositeProblem(parameter_df: pandas.core.frame.DataFrame = None,
                                                problems: List[petab.problem.Problem] = None)
```

Bases: object

Representation of a PETab problem consisting of multiple models

problems

List petab.Problems

parameter_df

PETab parameter DataFrame

```
static from_yaml(yaml_config: Union[Dict[KT, VT], str]) → petab.composite_problem.CompositeProblem
```

Create from YAML file

Factory method to create a CompositeProblem instance from a PETab YAML config file

Parameters **yaml_config** – PETab configuration as dictionary or YAML file name

11.3 petab.core

PETab core functions (or functions that don't fit anywhere else)

Functions

<code>concat_tables</code> (tables, ...)	Concatenate DataFrames provided as DataFrames or filenames, and a parser
<code>create_combine_archive</code> (yaml_file, filename, ...)	Create COMBINE archive (http://co.mbine.org/documents/archive) based on PETab YAML file.
<code>flatten_timepoint_specific_output_overrides</code>	Flatten timepoint-specific output parameter overrides.
<code>get_notnull_columns</code> (df, candidates)	Return list of df-columns in candidates which are not all null/nan.
<code>get_observable_id</code> (parameter_id)	Get PETab observable ID from PETab-style sigma or observable <i>AssignmentRule</i> -target parameter_id.
<code>get_simulation_df</code> (simulation_file)	Read PETab simulation table

Continued on next page

Table 3 – continued from previous page

<code>get_visualization_df(visualization_file)</code>	Read PEOab visualization table
<code>is_empty(val)</code>	Check if the value <i>val</i> , e.g.
<code>to_float_if_float(x)</code>	Return input as float if possible, otherwise return as is
<code>unique_preserve_order(seq)</code>	Return a list of unique elements in Sequence, keeping only the first occurrence of each element
<code>write_simulation_df(df, filename)</code>	Write PEOab simulation table
<code>write_visualization_df(df, filename)</code>	Write PEOab visualization table

`petab.core.concat_tables` (*tables*: *Union[str, pandas.core.frame.DataFrame, Iterable[Union[pandas.core.frame.DataFrame, str]]]*, *file_parser*: *Optional[Callable] = None*) \rightarrow *pandas.core.frame.DataFrame*
Concatenate DataFrames provided as DataFrames or filenames, and a parser

Parameters

- **tables** – Iterable of tables to join, as DataFrame or filename.
- **file_parser** – Function used to read the table in case filenames are provided, accepting a filename as only argument.

Returns The concatenated DataFrames

`petab.core.create_combine_archive` (*yaml_file*: *str*, *filename*: *str*, *family_name*: *Optional[str] = None*, *given_name*: *Optional[str] = None*, *email*: *Optional[str] = None*, *organization*: *Optional[str] = None*) \rightarrow *None*
Create COMBINE archive (<http://co.mbine.org/documents/archive>) based on PEOab YAML file.

Parameters

- **yaml_file** – Path to PEOab YAML file
- **family_name** – Family name of archive creator
- **given_name** – Given name of archive creator
- **email** – E-mail address of archive creator
- **organization** – Organization of archive creator

`petab.core.flatten_timepoint_specific_output_overrides` (*petab_problem*: *petab.problem.Problem*) \rightarrow *None*
Flatten timepoint-specific output parameter overrides.

If the PEOab problem definition has timepoint-specific *observableParameters* or *noiseParameters* for the same observable, replace those by replicating the respective observable.

This is a helper function for some tools which may not support such timepoint-specific mappings. The observable table and measurement table are modified in place.

Parameters **petab_problem** – PEOab problem to work on

`petab.core.get_notnull_columns` (*df*: *pandas.core.frame.DataFrame*, *candidates*: *Iterable[T_co]*)
Return list of df-columns in *candidates* which are not all null/nan.

The output can e.g. be used as input for `pandas.DataFrame.groupby`.

Parameters

- **df** – Dataframe
- **candidates** – Columns of df to consider

`petab.core.get_observable_id(parameter_id: str) → str`

Get PEtAb observable ID from PEtAb-style sigma or observable *AssignmentRule*-target `parameter_id`.

e.g. for 'observable_obs1' -> 'obs1', for 'sigma_obs1' -> 'obs1'

Parameters `parameter_id` – Some parameter ID

Returns Observable ID

`petab.core.get_simulation_df(simulation_file: str) → pandas.core.frame.DataFrame`

Read PEtAb simulation table

Parameters `simulation_file` – URL or filename of PEtAb simulation table

Returns Simulation DataFrame

`petab.core.get_visualization_df(visualization_file: str) → pandas.core.frame.DataFrame`

Read PEtAb visualization table

Parameters `visualization_file` – URL or filename of PEtAb visualization table

Returns Visualization DataFrame

`petab.core.is_empty(val) → bool`

Check if the value `val`, e.g. a table entry, is empty.

Parameters `val` – The value to check.

Returns Whether the field is to be considered empty.

Return type empty

`petab.core.to_float_if_float(x: Any) → Any`

Return input as float if possible, otherwise return as is

Parameters `x` – Anything

Returns `x` as float if possible, otherwise `x`

`petab.core.unique_preserve_order(seq: Sequence[T_co]) → List[T]`

Return a list of unique elements in Sequence, keeping only the first occurrence of each element

`seq`: Sequence to prune

Returns List of unique elements in `seq`

`petab.core.write_simulation_df(df: pandas.core.frame.DataFrame, filename: str) → None`

Write PEtAb simulation table

Parameters

- **df** – PEtAb simulation table
- **filename** – Destination file name

`petab.core.write_visualization_df(df: pandas.core.frame.DataFrame, filename: str) → None`

Write PEtAb visualization table

Parameters

- **df** – PEtAb visualization table
- **filename** – Destination file name

11.4 petab.conditions

Functions operating on the PEOtab condition table

Functions

<code>create_condition_df(parameter_ids, condition_ids)</code>	Create empty condition DataFrame
<code>get_condition_df(condition_file, ...)</code>	Read the provided condition file into a pandas.DataFrame
<code>get_parametric_overrides(condition_df)</code>	Get parametric overrides from condition table
<code>write_condition_df(df, filename)</code>	Write PEOtab condition table

```
petab.conditions.create_condition_df(parameter_ids: Iterable[str], condition_ids:
Optional[Iterable[str]] = None) → pandas.core.frame.DataFrame
```

Create empty condition DataFrame

Parameters

- **parameter_ids** – the columns
- **condition_ids** – the rows

Returns A pandas.DataFrame with empty given rows and columns and all nan values

```
petab.conditions.get_condition_df(condition_file: Union[str, pandas.core.frame.DataFrame,
None]) → pandas.core.frame.DataFrame
```

Read the provided condition file into a pandas.DataFrame

Conditions are rows, parameters are columns, conditionId is index.

Parameters **condition_file** – File name of PEOtab condition file or pandas.DataFrame

```
petab.conditions.get_parametric_overrides(condition_df: pandas.core.frame.DataFrame)
→ List[str]
```

Get parametric overrides from condition table

Parameters **condition_df** – PEOtab condition table

Returns List of parameter IDs that are mapped in a condition-specific way

```
petab.conditions.write_condition_df(df: pandas.core.frame.DataFrame, filename: str) →
None
```

Write PEOtab condition table

Parameters

- **df** – PEOtab condition table
- **filename** – Destination file name

11.5 petab.C

This file contains constant definitions.

11.6 petab.lint

Integrity checks and tests for specific features used

Functions

<code>assert_all_parameters_present_in_parameter_table(sbml_model, parameter_table)</code>	Ensure that all required parameters are contained in the parameter table with no additional ones
<code>assert_measured_observables_defined(measurement_table, observable_table)</code>	Check if all observables in the measurement table have been defined in the observable table
<code>assert_measurement_conditions_present_in_condition_table(condition_table, measurement_df, simulationConditionId, measurement_df, preequilibrationConditionId)</code>	Ensure that all entries from measurement_df.simulationConditionId and measurement_df.preequilibrationConditionId are present in condition_df.index.
<code>assert_model_parameters_in_condition_or_parameter_table(sbml_model, parameter_table, condition_table)</code>	Model parameters that are targets of AssignmentRule must not be present in parameter table or in condition table columns.
<code>assert_no_leading_trailing_whitespace(iterable)</code>	Check that there is no trailing whitespace in elements of Iterable
<code>assert_noise_distributions_valid(observable_df)</code>	Ensure that noise distributions and transformations for observables are valid.
<code>assert_parameter_bounds_are_numeric(parameter_df)</code>	Check if all entries in the lowerBound and upperBound columns of the parameter table are numeric.
<code>assert_parameter_estimate_is_boolean(parameter_df)</code>	Check if all entries in the estimate column of the parameter table are 0 or 1.
<code>assert_parameter_id_is_string(parameter_df)</code>	Check if all entries in the parameterId column of the parameter table are string and not empty.
<code>assert_parameter_id_is_unique(parameter_df)</code>	Check if the parameterId column of the parameter table is unique.
<code>assert_parameter_prior_parameters_are_valid(parameter_df)</code>	Check that the prior parameters are valid.
<code>assert_parameter_prior_type_is_valid(parameter_df)</code>	Check that valid prior types have been selected
<code>assert_parameter_scale_is_valid(parameter_df)</code>	Check if all entries in the parameterScale column of the parameter table are 'lin' for linear, 'log' for natural logarithm or 'log10' for base 10 logarithm.
<code>check_condition_df(df, sbml_model)</code>	Run sanity checks on PEtAb condition table
<code>check_ids(ids, kind)</code>	Check IDs are valid
<code>check_measurement_df(df, observable_df)</code>	Run sanity checks on PEtAb measurement table
<code>check_observable_df(observable_df)</code>	Check validity of observable table
<code>check_parameter_bounds(parameter_df)</code>	Check if all entries in the lowerBound are smaller than upperBound column in the parameter table and that bounds are positive for parameterScale log/log10.
<code>check_parameter_df(df, sbml_model, ...)</code>	Run sanity checks on PEtAb parameter table
<code>condition_table_is_parameter_free(condition_table)</code>	Check if all entries in the condition table are numeric (no parameter IDs)
<code>is_valid_identifier(x)</code>	Check whether <i>x</i> is a valid identifier
<code>lint_problem(problem)</code>	Run PEtAb validation on problem
<code>measurement_table_has_observable_parameters_to_override(measurement_table)</code>	Are there any numbers to override observable parameters?
<code>measurement_table_has_timepoint_specifications(measurement_table)</code>	Are there time (point) or replicate specific parameter assignments in the measurement table.

`petab.lint._check_df(df: pandas.core.frame.DataFrame, req_cols: Iterable[T_co], name: str) → None`

Check if given columns are present in DataFrame

Parameters

- **df** – Dataframe to check
- **req_cols** – Column names which have to be present
- **name** – Name of the DataFrame to be included in error message

Raises `AssertionError` – if a column is missing

`petab.lint.assert_all_parameters_present_in_parameter_df(parameter_df: pandas.core.frame.DataFrame, sbml_model: libsbml.Model, observable_df: pandas.core.frame.DataFrame, measurement_df: pandas.core.frame.DataFrame, condition_df: pandas.core.frame.DataFrame) → None`

Ensure all required parameters are contained in the parameter table with no additional ones

Parameters

- **parameter_df** – PEtab parameter DataFrame
- **sbml_model** – PEtab SBML Model
- **observable_df** – PEtab observable table
- **measurement_df** – PEtab measurement table
- **condition_df** – PEtab condition table

Raises `AssertionError` – in case of problems

`petab.lint.assert_measured_observables_defined(measurement_df: pandas.core.frame.DataFrame, observable_df: pandas.core.frame.DataFrame) → None`

Check if all observables in the measurement table have been defined in the observable table

Parameters

- **measurement_df** – PEtab measurement table
- **observable_df** – PEtab observable table

Raises `AssertionError` – in case of problems

`petab.lint.assert_measurement_conditions_present_in_condition_table(measurement_df: pandas.core.frame.DataFrame, condition_df: pandas.core.frame.DataFrame) → None`

Ensure that all entries from `measurement_df.simulationConditionId` and `measurement_df.preequilibrationConditionId` are present in `condition_df.index`.

Parameters

- **measurement_df** – PEtAb measurement table
- **condition_df** – PEtAb condition table

Raises `AssertionError` – in case of problems

```
petab.lint.assert_model_parameters_in_condition_or_parameter_table (sbml_model:
                                                                    libs-
                                                                    bml.Model,
                                                                    condi-
                                                                    tion_df:
                                                                    pan-
                                                                    das.core.frame.DataFrame,
                                                                    param-
                                                                    eter_df:
                                                                    pan-
                                                                    das.core.frame.DataFrame)
                                                                    → None
```

Model parameters that are targets of `AssignmentRule` must not be present in parameter table or in condition table columns. Other parameters must only be present in either in parameter table or condition table columns. Check that.

Parameters

- **parameter_df** – PEtAb parameter `DataFrame`
- **sbml_model** – PEtAb SBML Model
- **condition_df** – PEtAb condition table

Raises `AssertionError` – in case of problems

```
petab.lint.assert_no_leading_trailing_whitespace (names_list: Iterable[str], name: str)
                                                                    → None
```

Check that there is no trailing whitespace in elements of `Iterable`

Parameters

- **names_list** – strings to check for whitespace
- **name** – name of `names_list` for error messages

Raises `AssertionError` – if there is trailing whitespace

```
petab.lint.assert_noise_distributions_valid (observable_df:
                                                                    pan-
                                                                    das.core.frame.DataFrame) → None
```

Ensure that noise distributions and transformations for observables are valid.

Parameters **observable_df** – PEtAb observable table

Raises `AssertionError` – in case of problems

```
petab.lint.assert_parameter_bounds_are_numeric (parameter_df:
                                                                    pan-
                                                                    das.core.frame.DataFrame) → None
```

Check if all entries in the `lowerBound` and `upperBound` columns of the parameter table are numeric.

Parameters **parameter_df** – PEtAb parameter `DataFrame`

Raises `AssertionError` – in case of problems

```
petab.lint.assert_parameter_estimate_is_boolean (parameter_df:
                                                                    pan-
                                                                    das.core.frame.DataFrame) →
                                                                    None
```

Check if all entries in the `estimate` column of the parameter table are 0 or 1.

Parameters `parameter_df` – PEtab parameter DataFrame

Raises `AssertionError` – in case of problems

`petab.lint.assert_parameter_id_is_string` (`parameter_df`: `pandas.core.frame.DataFrame`)
→ None

Check if all entries in the `parameterId` column of the parameter table are string and not empty.

Parameters `parameter_df` – PEtab parameter DataFrame

Raises `AssertionError` – in case of problems

`petab.lint.assert_parameter_id_is_unique` (`parameter_df`: `pandas.core.frame.DataFrame`)
→ None

Check if the `parameterId` column of the parameter table is unique.

Parameters `parameter_df` – PEtab parameter DataFrame

Raises `AssertionError` – in case of problems

`petab.lint.assert_parameter_prior_parameters_are_valid` (`parameter_df`: `pandas.core.frame.DataFrame`)
→ None

Check that the prior parameters are valid.

Parameters `parameter_df` – PEtab parameter table

Raises `AssertionError` in case of invalide prior parameters

`petab.lint.assert_parameter_prior_type_is_valid` (`parameter_df`: `pandas.core.frame.DataFrame`)
→ None

Check that valid prior types have been selected

Parameters `parameter_df` – PEtab parameter table

Raises `AssertionError` in case of invalid prior

`petab.lint.assert_parameter_scale_is_valid` (`parameter_df`: `pandas.core.frame.DataFrame`) → None

Check if all entries in the `parameterScale` column of the parameter table are ‘lin’ for linear, ‘log’ for natural logarithm or ‘log10’ for base 10 logarithm.

Parameters `parameter_df` – PEtab parameter DataFrame

Raises `AssertionError` – in case of problems

`petab.lint.check_condition_df` (`df`: `pandas.core.frame.DataFrame`, `sbml_model`: `Optional[libsbml.Model]`) → None

Run sanity checks on PEtab condition table

Parameters

- `df` – PEtab condition DataFrame
- `sbml_model` – SBML Model for additional checking of parameter IDs

Raises `AssertionError` – in case of problems

`petab.lint.check_ids` (`ids`: `Iterable[str]`, `kind`: `str` = “”) → None

Check IDs are valid

Parameters

- `ids` – Iterable of IDs to check
- `kind` – Kind of IDs, for more informative error message

Raises `ValueError` - in case of invalid IDs

`petab.lint.check_measurement_df` (*df*: *pandas.core.frame.DataFrame*, *observable_df*: *Optional[pandas.core.frame.DataFrame]* = *None*) → *None*

Run sanity checks on PEOtab measurement table

Parameters

- **df** – PEOtab measurement DataFrame
- **observable_df** – PEOtab observable DataFrame for checking if measurements are compatible with observable transformations.

Raises *AssertionError*, *ValueError* – in case of problems

`petab.lint.check_observable_df` (*observable_df*: *pandas.core.frame.DataFrame*) → *None*

Check validity of observable table

Parameters **observable_df** – PEOtab observable DataFrame

Raises *AssertionError* – in case of problems

`petab.lint.check_parameter_bounds` (*parameter_df*: *pandas.core.frame.DataFrame*) → *None*

Check if all entries in the lowerBound are smaller than upperBound column in the parameter table and that bounds are positive for parameterScale loglog10.

Parameters **parameter_df** – PEOtab parameter DataFrame

Raises *AssertionError* – in case of problems

`petab.lint.check_parameter_df` (*df*: *pandas.core.frame.DataFrame*, *sbml_model*: *Optional[libsbml.Model]* = *None*, *observable_df*: *Optional[pandas.core.frame.DataFrame]* = *None*, *measurement_df*: *Optional[pandas.core.frame.DataFrame]* = *None*, *condition_df*: *Optional[pandas.core.frame.DataFrame]* = *None*) → *None*

Run sanity checks on PEOtab parameter table

Parameters

- **df** – PEOtab condition DataFrame
- **sbml_model** – SBML Model for additional checking of parameter IDs
- **observable_df** – PEOtab observable table for additional checks
- **measurement_df** – PEOtab measurement table for additional checks
- **condition_df** – PEOtab condition table for additional checks

Raises *AssertionError* – in case of problems

`petab.lint.condition_table_is_parameter_free` (*condition_df*: *pandas.core.frame.DataFrame*) → *bool*

Check if all entries in the condition table are numeric (no parameter IDs)

Parameters **condition_df** – PEOtab condition table

Returns True if there are no parameter overrides in the condition table, False otherwise.

`petab.lint.is_valid_identifier` (*x*: *str*) → *bool*

Check whether *x* is a valid identifier

Check whether *x* is a valid identifier for conditions, parameters, observables... . Identifiers may contain upper and lower case letters, digits and underscores, but must not start with a digit.

Parameters **x** – string to check

Returns True if valid, False otherwise

`petab.lint.lint_problem(problem: petab.problem.Problem) → bool`
 Run PETab validation on problem

Parameters `problem` – PETab problem to check

Returns True is errors occurred, False otherwise

`petab.lint.measurement_table_has_observable_parameter_numeric_overrides(measurement_df: pandas.core.frame.DataFrame) → bool`
 Are there any numbers to override observable parameters?

Parameters `measurement_df` – PETab measurement table

Returns True if there any numbers to override observable parameters, False otherwise.

`petab.lint.measurement_table_has_timepoint_specific_mappings(measurement_df: pandas.core.frame.DataFrame) → bool`
 Are there time-point or replicate specific parameter assignments in the measurement table.

Parameters `measurement_df` – PETab measurement table

Returns True if there are time-point or replicate specific parameter assignments in the measurement table, False otherwise.

11.7 petab.measurements

Functions operating on the PETab measurement table

Functions

<code>assert_overrides_match_parameter_count(measurement_df)</code>	Ensure that number of parameters in the observable definition matches the number of overrides in <code>measurement_df</code>
<code>create_measurement_df()</code>	Create empty measurement dataframe
<code>get_measurement_df(measurement_file, str, ...)</code>	Read the provided measurement file into a pandas.DataFrame.
<code>get_measurement_parameter_ids(measurement_df)</code>	Return list of ID of parameters which occur in measurement table as observable or noise parameter overrides.
<code>get_noise_distributions(measurement_df)</code>	Returns dictionary of cost definitions per observable, if specified.
<code>get_rows_for_condition(measurement_df, ...)</code>	Extract rows in <code>measurement_df</code> for <code>condition</code> according to 'preequilibrationConditionId' and 'simulationConditionId' in <code>condition</code> .
<code>get_simulation_conditions(measurement_df)</code>	Create a table of separate simulation conditions.
<code>measurements_have_replicates(measurement_df)</code>	Tests whether the measurements come with replicates
<code>split_parameter_replacement_list(...)</code>	Split values in observableParameters and noiseParameters in measurement table.
<code>write_measurement_df(df, filename)</code>	Write PETab measurement table

```
petab.measurements.assert_overrides_match_parameter_count (measurement_df: pandas.core.frame.DataFrame,
                                                            observable_df: pandas.core.frame.DataFrame)
                                                            → None
```

Ensure that number of parameters in the observable definition matches the number of overrides in measurement_df

Parameters

- **measurement_df** – PEtab measurement table
- **observable_df** – PEtab observable table

```
petab.measurements.create_measurement_df () → pandas.core.frame.DataFrame
```

Create empty measurement dataframe

Returns Created DataFrame

```
petab.measurements.get_measurement_df (measurement_file: Union[None, str, pandas.core.frame.DataFrame]) → pandas.core.frame.DataFrame
```

Read the provided measurement file into a pandas.DataFrame.

Parameters **measurement_file** – Name of file to read from or pandas.DataFrame

Returns Measurement DataFrame

```
petab.measurements.get_measurement_parameter_ids (measurement_df: pandas.core.frame.DataFrame) → List[str]
```

Return list of ID of parameters which occur in measurement table as observable or noise parameter overrides.

Parameters **measurement_df** – PEtab measurement DataFrame

Returns List of parameter IDs

```
petab.measurements.get_noise_distributions (measurement_df: pandas.core.frame.DataFrame) → dict
```

Returns dictionary of cost definitions per observable, if specified.

Looks through all parameters satisfying *sbml_parameter_is_cost* and return as dictionary.

Parameters **measurement_df** – PEtab measurement table

Returns Dictionary with *observableId* => *cost definition*

```
petab.measurements.get_rows_for_condition (measurement_df: pandas.core.frame.DataFrame, condition: Union[pandas.core.frame.DataFrame, Dict[KT, VT]]) → pandas.core.frame.DataFrame
```

Extract rows in *measurement_df* for *condition* according to 'preequilibrationConditionId' and 'simulationConditionId' in *condition*.

Parameters

- **measurement_df** – PEtab measurement DataFrame
- **condition** – DataFrame with single row and columns 'preequilibrationConditionId' and 'simulationConditionId'. Or dictionary with those keys.

Returns The subselection of rows in measurement_df for the condition

condition.

`petab.measurements.get_simulation_conditions` (*measurement_df: das.core.frame.DataFrame*) → *pan-das.core.frame.DataFrame*
 Create a table of separate simulation conditions. A simulation condition is a specific combination of simulation-ConditionId and preequilibrationConditionId.

Parameters `measurement_df` – PEtab measurement table

Returns Dataframe with columns ‘simulationConditionId’ and ‘preequilibrationConditionId’. All-null columns will be omitted. Missing ‘preequilibrationConditionId’s will be set to ‘’ (empty string).

`petab.measurements.measurements_have_replicates` (*measurement_df: das.core.frame.DataFrame*) → *bool*
 Tests whether the measurements come with replicates

Parameters `measurement_df` – Measurement table

Returns True if there are replicates, False otherwise

`petab.measurements.split_parameter_replacement_list` (*list_string: Union[str, numbers.Number]*, *delim: str = ';'*) → *List[Union[str, float]]*
 Split values in observableParameters and noiseParameters in measurement table.

Parameters

- **list_string** – delim-separated stringified list
- **delim** – delimiter

Returns List of split values. Numeric values converted to float.

`petab.measurements.write_measurement_df` (*df: pandas.core.frame.DataFrame*, *filename: str*) → *None*
 Write PEtab measurement table

Parameters

- **df** – PEtab measurement table
- **filename** – Destination file name

11.8 petab.parameter_mapping

Functions related to mapping parameter from model to parameter estimation problem

Functions

<code>get_optimization_to_simulation_parameter_mapping(...)</code>	Create list of mapping dicts from PEtab-problem to SBML parameters.
<code>get_parameter_mapping_for_condition(...)</code>	Create dictionary of parameter value and parameter scale mappings from PEtab-problem to SBML parameters for the given condition.
<code>handle_missing_overrides(...)</code>	Find all observable parameters and noise parameters that were not mapped and set their mapping to np.nan.

Continued on next page

Table 7 – continued from previous page

<code>merge_preeq_and_sim_pars</code> (parameter_mappings, ...)	Merge preequilibration and simulation parameters and scales for a list of conditions while checking for compatibility.
<code>merge_preeq_and_sim_pars_condition</code> (...)	Merge preequilibration and simulation parameters and scales for a single condition while checking for compatibility.

`petab.parameter_mapping._apply_condition_parameters` (*par_mapping*: *Dict[str, Union[str, numbers.Number]]*, *scale_mapping*: *Dict[str, str]*, *condition_id*: *str*, *condition_df*: *pandas.core.frame.DataFrame*, *sbml_model*: *libsbml.Model*) → *None*

Replace parameter IDs in parameter mapping dictionary by condition table parameter values (in-place).

Parameters

- **par_mapping** – see `get_parameter_mapping_for_condition`
- **condition_id** – ID of condition to work on
- **condition_df** – PEtab condition table

`petab.parameter_mapping._apply_output_parameter_overrides` (*mapping*: *Dict[str, Union[str, numbers.Number]]*, *cur_measurement_df*: *pandas.core.frame.DataFrame*) → *None*

Apply output parameter overrides to the parameter mapping dict for a given condition as defined in the measurement table (`observableParameter`, `noiseParameters`).

Parameters

- **mapping** – parameter mapping dict as obtained from `get_parameter_mapping_for_condition`
- **cur_measurement_df** – Subset of the measurement table for the current condition

`petab.parameter_mapping._apply_overrides_for_observable` (*mapping*: *Dict[str, Union[str, numbers.Number]]*, *observable_id*: *str*, *override_type*: *str*, *overrides*: *List[str]*) → *None*

Apply parameter-overrides for observables and noises to mapping matrix.

Parameters

- **mapping** – mapping dict to which to apply overrides
- **observable_id** – observable ID
- **override_type** – ‘observable’ or ‘noise’
- **overrides** – list of overrides for noise or observable parameters


```
petab.parameter_mapping._apply_parameter_table (par_mapping: Dict[str, Union[str,
numbers.Number]], scale_mapping: Dict[str, str], parameter_df: Optional[pandas.core.frame.DataFrame]
= None, scaled_parameters: bool = False) → None
```

Replace parameters from parameter table in mapping list for a given condition and set the corresponding scale.

Replace non-estimated parameters by `nominalValues` (un-scaled / lin-scaled), replace estimated parameters by the respective ID.

Parameters

- **par_mapping** – mapping dict obtained from `get_parameter_mapping_for_condition`
- **parameter_df** – PEtAb parameter table

```
petab.parameter_mapping._map_condition (packed_args)
```

Helper function for parallel condition mapping.

For arguments see `get_optimization_to_simulation_parameter_mapping`

```
petab.parameter_mapping._map_condition_arg_packer (simulation_conditions, measurement_df, condition_df, parameter_df, sbml_model, simulation_parameters, warn_unmapped, scaled_parameters)
```

Helper function to pack extra arguments for `_map_condition`

```
petab.parameter_mapping._output_parameters_to_nan (mapping: Dict[str, Union[str, numbers.Number]]) → None
```

Set output parameters in mapping dictionary to nan

```
petab.parameter_mapping._perform_mapping_checks (measurement_df: pandas.core.frame.DataFrame) → None
```

Check for PEtAb features which we can't account for during parameter mapping.

```

petab.parameter_mapping.get_optimization_to_simulation_parameter_mapping(condition_df:
    pandas.core.frame.DataFrame,
    measurement_df:
    pandas.core.frame.DataFrame,
    parameter_df:
    pandas.core.frame.DataFrame,
    optional_parameter_df:
    Optional[pandas.core.frame.DataFrame],
    sbml_model:
    Optional[libsbml.Model],
    simulation_conditions:
    Optional[pandas.core.frame.DataFrame],
    warn_unmapped:
    Optional[bool],
    scaled_parameters:
    bool,
    False)
    →
    List[Tuple[Dict[str,
    Union[str,
    numbers.Number]],
    Dict[str,
    Union[str,
    numbers.Number]],
    Dict[str,
    Union[str,
    numbers.Number]]]]

```

Create list of mapping dicts from PEtap-problem to SBML parameters.

Mapping can be performed in parallel. The number of threads is controlled by the environment variable with the name of `petab.ENV_NUM_THREADS`.

Parameters

- **measurement_df, parameter_df, observable_df** (*condition_df*,) – The dataframes in the PEtap format.
- **sbml_model** – The sbml model with observables and noise specified according to the PEtap format.
- **simulation_conditions** – Table of simulation conditions as created by `petab.get_simulation_conditions`.
- **warn_unmapped** – If `True`, log warning regarding unmapped parameters
- **scaled_parameters** – Whether parameter values should be scaled.

Returns

Parameter value and parameter scale mapping for all conditions.

The length of the returned array is the number of unique combinations of `simulationConditionId`'s and `preequilibrationConditionId`'s from the measurement table. Each entry is a tuple of four dicts of length equal to the number of model parameters. The first two dicts map simulation parameter IDs to optimization parameter IDs or values (where values are fixed) for preequilibration and simulation condition, respectively. The last two dicts map simulation parameter IDs to the parameter scale of the respective parameter, again for preequilibration and simulation condition. If no preequilibration condition is defined, the respective dicts will be empty. `NaN` is used where no mapping exists.

```
petab.parameter_mapping.get_parameter_mapping_for_condition(condition_id: str,
                                                            is_preeq: bool,
                                                            cur_measurement_df:
                                                                pandas.core.frame.DataFrame,
                                                            sbml_model:
                                                                libsbml.Model,
                                                            condition_df: pandas.core.frame.DataFrame,
                                                            parameter_df: pandas.core.frame.DataFrame
                                                                = None, simulation_parameters:
                                                                Optional[Dict[str,
                                                                str]] = None,
                                                            warn_unmapped:
                                                                bool = True,
                                                            scaled_parameters:
                                                                bool = False)
    → Tuple[Dict[str,
    Union[str, numbers.Number]],
    Dict[str, str]]
```

Create dictionary of parameter value and parameter scale mappings from PÉtab-problem to SBML parameters for the given condition.

Parameters

- **condition_id** – Condition ID for which to perform mapping
- **is_preeq** – If `True`, output parameters will not be mapped
- **cur_measurement_df** – Measurement sub-table for current condition
- **condition_df** – PÉtab condition DataFrame
- **parameter_df** – PÉtab parameter DataFrame
- **sbml_model** – The sbml model with observables and noise specified according to the PÉtab format used to retrieve simulation parameter IDs.
- **simulation_parameters** – Model simulation parameter IDs mapped to parameter values (output of `petab.sbml.get_model_parameters(..., with_values=True)`). Optional, saves time if precomputed.
- **warn_unmapped** – If `True`, log warning regarding unmapped parameters

Returns Tuple of two dictionaries. First dictionary mapping model parameter IDs to mapped parameters IDs to be estimated or to filled-in values in case of non-estimated parameters. Second dictionary mapping model parameter IDs to their scale. NaN is used where no mapping exists.

```
petab.parameter_mapping.handle_missing_overrides(mapping_par_opt_to_par_sim:
                                                Dict[str, Union[str, num-
                                                                bers.Number]], warn: bool =
                                                True, condition_id: str = None) →
                                                None
```

Find all observable parameters and noise parameters that were not mapped and set their mapping to `np.nan`.

Assumes that parameters matching “(noiselobservable)Parameter[0-9]+_” were all supposed to be overwritten.

Parameters

- **mapping_par_opt_to_par_sim** – Output of `get_parameter_mapping_for_condition`
- **warn** – If `True`, log warning regarding unmapped parameters
- **condition_id** – Optional condition ID for more informative output

```
petab.parameter_mapping.merge_preeq_and_sim_pars(parameter_mappings: Iterable[Tuple[Dict[str,
                                                                                     Union[str,
                                                                                     numbers.Number]],
                                                                                     Dict[str,
                                                                                     Union[str,
                                                                                     numbers.Number]]]],
                                                scale_mappings: Iterable[Tuple[Dict[str,
                                                                                     str],
                                                                                     Dict[str,
                                                                                     Union[str,
                                                                                     numbers.Number]],
                                                                                     Dict[str,
                                                                                     Union[str,
                                                                                     numbers.Number]]],
                                                                                     List[Tuple[Dict[str,
                                                                                     str],
                                                                                     Dict[str,
                                                                                     str]]]]) → Tuple[List[Tuple[Dict[str,
                                                                                     Union[str,
                                                                                     numbers.Number]],
                                                                                     Dict[str,
                                                                                     Union[str,
                                                                                     numbers.Number]]],
                                                                                     List[Tuple[Dict[str,
                                                                                     str],
                                                                                     Dict[str,
                                                                                     str]]]]]
```

Merge preequilibrium and simulation parameters and scales for a list of conditions while checking for compatibility.

Parameters

- **parameter_mappings** – As returned by `petab.get_optimization_to_simulation_parameter_mapping`
- **scale_mappings** – As returned by `petab.get_optimization_to_simulation_scale_mapping`.

Returns The parameter and scale simulation mappings, modified and checked.

```
petab.parameter_mapping.merge_preeq_and_sim_pars_condition(condition_map_preeq:
    Dict[str, Union[str,
    numbers.Number]],
    condition_map_sim:
    Dict[str,
    Union[str, num-
    bers.Number]], condi-
    tion_scale_map_preeq:
    Dict[str, str], condi-
    tion_scale_map_sim:
    Dict[str, str], con-
    dition: Any) →
    None
```

Merge preequilibration and simulation parameters and scales for a single condition while checking for compatibility.

This function is meant for the case where we cannot have different parameters (and scales) for preequilibration and simulation. Therefore, merge both and ensure matching scales and parameters. `condition_map_sim` and `condition_scale_map_sim` will ne modified in place.

Parameters

- **condition_map_sim**(*condition_map_preeq*,) – Parameter mapping as obtained from *get_parameter_mapping_for_condition*
- **condition_scale_map_sim** (*condition_scale_map_preeq*,) – Parameter scale mapping as obtained from *get_get_scale_mapping_for_condition*
- **condition** – Condition identifier for more informative error messages

11.9 petab.parameters

Functions operating on the PEOtab parameter table

Functions

<code>create_parameter_df(sbml_model, ...)</code>	Create a new PEOtab parameter table
<code>get_optimization_parameter_scaling(parameter_df)</code>	Get dictionary with optimization parameter IDs mapped to parameter scaling strings.
<code>get_optimization_parameters(parameter_df)</code>	Get list of optimization parameter IDs from parameter table.
<code>get_parameter_df(parameter_file, ...)</code>	Read the provided parameter file into a pandas. Dataframe.
<code>get_priors_from_df(parameter_df, mode)</code>	Create list with information about the parameter priors
<code>get_required_parameters_for_parameter_table(parameter_df)</code>	Get set of parameters which need to go into the parameter table
<code>get_valid_parameters_for_parameter_table(parameter_df)</code>	Get set of parameters which may be present inside the parameter table
<code>map_scale(parameters, scale_strs)</code>	As <code>scale()</code> , but for Iterables
<code>normalize_parameter_df(parameter_df)</code>	Add missing columns and fill in default values.
<code>scale(parameter, scale_str)</code>	Scale parameter according to <code>scale_str</code>

Continued on next page

Table 8 – continued from previous page

<code>unscale(parameter, scale_str)</code>	Unscale parameter according to scale_str
<code>write_parameter_df(df, filename)</code>	Write PEtAb parameter table

`petab.parameters.create_parameter_df` (*sbml_model: libsbml.Model, condition_df: pandas.core.frame.DataFrame, observable_df: pandas.core.frame.DataFrame, measurement_df: pandas.core.frame.DataFrame, include_optional: bool = False, parameter_scale: str = 'log10', lower_bound: Iterable[T_co] = None, upper_bound: Iterable[T_co] = None*) → `pandas.core.frame.DataFrame`

Create a new PEtAb parameter table

All table entries can be provided as string or list-like with length matching the number of parameters

Parameters

- **sbml_model** – SBML Model
- **condition_df** – PEtAb condition DataFrame
- **measurement_df** – PEtAb measurement DataFrame
- **include_optional** – By default this only returns parameters that are required to be present in the parameter table. If set to True, this returns all parameters that are allowed to be present in the parameter table (i.e. also including parameters specified in the SBML model).
- **parameter_scale** – parameter scaling
- **lower_bound** – lower bound for parameter value
- **upper_bound** – upper bound for parameter value

Returns The created parameter DataFrame

`petab.parameters.get_optimization_parameter_scaling` (*parameter_df: pandas.core.frame.DataFrame*) → `Dict[str, str]`

Get Dictionary with optimization parameter IDs mapped to parameter scaling strings.

Parameters **parameter_df** – PEtAb parameter DataFrame

Returns Dictionary with optimization parameter IDs mapped to parameter scaling strings.

`petab.parameters.get_optimization_parameters` (*parameter_df: pandas.core.frame.DataFrame*) → `List[str]`

Get list of optimization parameter IDs from parameter table.

Parameters **parameter_df** – PEtAb parameter DataFrame

Returns List of IDs of parameters selected for optimization.

`petab.parameters.get_parameter_df` (*parameter_file: Union[str, pandas.core.frame.DataFrame, None]*) → `pandas.core.frame.DataFrame`

Read the provided parameter file into a `pandas.DataFrame`.

Parameters **parameter_file** – Name of the file to read from or `pandas.DataFrame`.

Returns Parameter DataFrame

`petab.parameters.get_priors_from_df` (*parameter_df: pandas.core.frame.DataFrame, mode: str*) → `List[Tuple]`

Create list with information about the parameter priors

Parameters

- **parameter_df** – PEtAb parameter table
- **mode** – ‘initialization’ or ‘objective’

Returns List with prior information.

```
petab.parameters.get_required_parameters_for_parameter_table(sbml_model:  
libsbml.Model,  
condition_df: pandas.core.frame.DataFrame,  
observable_df: pandas.core.frame.DataFrame,  
measurement_df: pandas.core.frame.DataFrame)  
→ Set[str]
```

Get set of parameters which need to go into the parameter table

Parameters

- **sbml_model** – PEtAb SBML model
- **condition_df** – PEtAb condition table
- **observable_df** – PEtAb observable table
- **measurement_df** – PEtAb measurement table

Returns Set of parameter IDs which PEtAb requires to be present in the parameter table. That is all {observable,noise}Parameters from the measurement table as well as all parametric condition table overrides that are not defined in the SBML model.

```
petab.parameters.get_valid_parameters_for_parameter_table(sbml_model: lib-  
sbml.Model, condition_df: pandas.core.frame.DataFrame,  
observable_df: pandas.core.frame.DataFrame,  
measurement_df: pandas.core.frame.DataFrame)  
→ Set[str]
```

Get set of parameters which may be present inside the parameter table

Parameters

- **sbml_model** – PEtAb SBML model
- **condition_df** – PEtAb condition table
- **observable_df** – PEtAb observable table
- **measurement_df** – PEtAb measurement table

Returns Set of parameter IDs which PEtAb allows to be present in the parameter table.

```
petab.parameters.map_scale(parameters: Iterable[numbers.Number], scale_strs: Iterable[str]) →  
Iterable[numbers.Number]
```

As scale(), but for Iterables

`petab.parameters.normalize_parameter_df` (*parameter_df: pandas.core.frame.DataFrame*) → *pandas.core.frame.DataFrame*

Add missing columns and fill in default values.

`petab.parameters.scale` (*parameter: numbers.Number, scale_str: str*) → *numbers.Number*
Scale parameter according to *scale_str*

Parameters

- **parameter** – Parameter to be scaled.
- **scale_str** – One of ‘lin’ (synonymous with ‘’), ‘log’, ‘log10’.

Returns The scaled parameter.

Return type *parameter*

`petab.parameters.unscale` (*parameter: numbers.Number, scale_str: str*) → *numbers.Number*
Unscale parameter according to *scale_str*

Parameters

- **parameter** – Parameter to be unscaled.
- **scale_str** – One of ‘lin’ (synonymous with ‘’), ‘log’, ‘log10’.

Returns The unscaled parameter.

Return type *parameter*

`petab.parameters.write_parameter_df` (*df: pandas.core.frame.DataFrame, filename: str*) → *None*

Write PEPtab parameter table

Parameters

- **df** – PEPtab parameter table
- **filename** – Destination file name

11.10 petab.problem

PEtab Problem class

Functions

<code>get_default_condition_file_name(model_name, ...)</code>	Get file name according to proposed convention
<code>get_default_measurement_file_name(...)</code>	Get file name according to proposed convention
<code>get_default_parameter_file_name(model_name, ...)</code>	Get file name according to proposed convention
<code>get_default_sbml_file_name(model_name, folder)</code>	Get file name according to proposed convention

Classes

<code>Problem(sbml_model, sbml_reader, ...)</code>	PEtab parameter estimation problem as defined by
--	--

```
class petab.problem.Problem(sbml_model: libsbml.Model = None, sbml_reader: libsbml.SBMLReader = None, sbml_document: libsbml.SBMLDocument = None, condition_df: pandas.core.frame.DataFrame = None, measurement_df: pandas.core.frame.DataFrame = None, parameter_df: pandas.core.frame.DataFrame = None, visualization_df: pandas.core.frame.DataFrame = None, observable_df: pandas.core.frame.DataFrame = None)
```

Bases: object

PEtab parameter estimation problem as defined by

- SBML model
- condition table
- measurement table
- parameter table
- observables table

Optionally it may contain visualization tables.

condition_df

PEtab condition table

measurement_df

PEtab measurement table

parameter_df

PEtab parameter table

observable_df

PEtab observable table

visualization_df

PEtab visualization table

sbml_reader

Stored to keep object alive.

sbml_document

Stored to keep object alive.

sbml_model

PEtab SBML model

_apply_mask (*v: List[T], free: bool = True, fixed: bool = True*)

Apply mask of only free or only fixed values.

Parameters

- **v** – The full vector the mask is to be applied to.
- **free** – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** – Whether to return fixed parameters, i.e. parameters not to estimate.

Returns The reduced vector with applied mask.

Return type *v*

create_parameter_df (**args, **kwargs*)

Create a new PEPtab parameter table

See create_parameter_df

static from_combine (*filename: str*) → petab.problem.Problem
 Read PETab COMBINE archive (<http://co.mbine.org/documents/archive>).

See also `create_combine_archive`.

Parameters **filename** – Path to the PETab-COMBINE archive

Returns A `petab.Problem` instance.

static from_files (*sbml_file: str = None, condition_file: str = None, measurement_file: Union[str, Iterable[str]] = None, parameter_file: str = None, visualization_files: Union[str, Iterable[str]] = None, observable_files: Union[str, Iterable[str]] = None*) → petab.problem.Problem

Factory method to load model and tables from files.

Parameters

- **sbml_file** – PETab SBML model
- **condition_file** – PETab condition table
- **measurement_file** – PETab measurement table
- **parameter_file** – PETab parameter table
- **visualization_files** – PETab visualization tables
- **observable_files** – PETab observables tables

static from_folder (*folder: str, model_name: str = None*) → petab.problem.Problem

Factory method to use the standard folder structure and file names, i.e.

```

${model_name}/
+-- experimentalCondition_${model_name}.tsv
+-- measurementData_${model_name}.tsv
+-- model_${model_name}.xml
+-- parameters_${model_name}.tsv
```

Parameters

- **folder** – Path to the directory in which the files are located.
- **model_name** – If specified, overrides the model component in the file names. Defaults to the last component of `folder`.

static from_yaml (*yaml_config: Union[Dict[KT, VT], str]*) → petab.problem.Problem

Factory method to load model and tables as specified by YAML file.

Parameters **yaml_config** – PETab configuration as dictionary or YAML file name

get_lb (*free: bool = True, fixed: bool = True, scaled: bool = False*)

Generic function to get lower parameter bounds.

Parameters

- **free** – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** – Whether to return fixed parameters, i.e. parameters not to estimate.
- **scaled** – Whether to scale the values according to the parameter scale, or return them on linear scale.

Returns The lower parameter bounds.

Return type `v`

get_model_parameters()
See `petab.sbml.get_model_parameters`

get_noise_distributions()
See `get_noise_distributions`.

get_observable_ids()
Returns dictionary of observable ids.

get_observables(remove: bool = False)
Returns dictionary of observables definitions. See `assignment_rules_to_dict` for details.

get_optimization_parameter_scales()
Return list of optimization parameter scaling strings.
See `petab.parameters.get_optimization_parameters`.

get_optimization_parameters()
Return list of optimization parameter IDs.
See `petab.parameters.get_optimization_parameters`.

get_optimization_to_simulation_parameter_mapping(warn_unmapped: bool = True, scaled_parameters: bool = False)
See `get_simulation_to_optimization_parameter_mapping`.

get_sigmas(remove: bool = False)
Return dictionary of observableId => sigma as defined in the SBML model. This does not include parameter mappings defined in the measurement table.

get_simulation_conditions_from_measurement_df()
See `petab.get_simulation_conditions`

get_ub(free: bool = True, fixed: bool = True, scaled: bool = False)
Generic function to get upper parameter bounds.

Parameters

- **free** – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** – Whether to return fixed parameters, i.e. parameters not to estimate.
- **scaled** – Whether to scale the values according to the parameter scale, or return them on linear scale.

Returns The upper parameter bounds.

Return type `v`

get_x_ids(free: bool = True, fixed: bool = True)
Generic function to get parameter ids.

Parameters

- **free** – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** – Whether to return fixed parameters, i.e. parameters not to estimate.

Returns The parameter ids.

Return type `v`

get_x_nominal(free: bool = True, fixed: bool = True, scaled: bool = False)
Generic function to get parameter nominal values.

Parameters

- **free** – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** – Whether to return fixed parameters, i.e. parameters not to estimate.
- **scaled** – Whether to scale the values according to the parameter scale, or return them on linear scale.

Returns The parameter nominal values.

Return type `v`

lb

Parameter table lower bounds.

lb_scaled

Parameter table lower bounds with applied parameter scaling

sample_parameter_startpoints (*n_starts: int = 100*)

Create starting points for optimization

See `sample_parameter_startpoints`

to_files (*sbml_file: Optional[str] = None, condition_file: Optional[str] = None, measurement_file: Optional[str] = None, parameter_file: Optional[str] = None, visualization_file: Optional[str] = None, observable_file: Optional[str] = None*) \rightarrow None

Write PEtAb tables to files for this problem

Writes PEtAb files for those entities for which a destination was passed.

NOTE: If this instance was created from multiple measurement or visualization tables, they will be merged and written to a single file.

Parameters

- **sbml_file** – SBML model destination
- **condition_file** – Condition table destination
- **measurement_file** – Measurement table destination
- **parameter_file** – Parameter table destination
- **visualization_file** – Visualization table destination
- **observable_file** – Observables table destination

Raises

- `ValueError` – If a destination was provided for a non-existing
- `entity`.

ub

Parameter table upper bounds

ub_scaled

Parameter table upper bounds with applied parameter scaling

x_fixed_ids

Parameter table parameter IDs, for fixed parameters.

x_fixed_indices

Parameter table non-estimated parameter indices.

x_free_ids

Parameter table parameter IDs, for free parameters.

x_free_indices

Parameter table estimated parameter indices.

x_ids

Parameter table parameter IDs

x_nominal

Parameter table nominal values

x_nominal_fixed

Parameter table nominal values, for fixed parameters.

x_nominal_fixed_scaled

Parameter table nominal values with applied parameter scaling, for fixed parameters.

x_nominal_free

Parameter table nominal values, for free parameters.

x_nominal_free_scaled

Parameter table nominal values with applied parameter scaling, for free parameters.

x_nominal_scaled

Parameter table nominal values with applied parameter scaling

`petab.problem.get_default_condition_file_name(model_name: str, folder: str = "")`

Get file name according to proposed convention

`petab.problem.get_default_measurement_file_name(model_name: str, folder: str = "")`

Get file name according to proposed convention

`petab.problem.get_default_parameter_file_name(model_name: str, folder: str = "")`

Get file name according to proposed convention

`petab.problem.get_default_sbml_file_name(model_name: str, folder: str = "")`

Get file name according to proposed convention

11.11 petab.sampling

Functions related to parameter sampling

Functions

<code>sample_from_prior(prior, list, str, list], ...)</code>	Creates samples for one parameter based on prior
<code>sample_parameter_startpoints(parameter_df, ...)</code>	Create numpy.array with starting points for an optimization

`petab.sampling.sample_from_prior(prior: Tuple[str, list, str, list], n_starts: int) → numpy.array`

Creates samples for one parameter based on prior

Parameters

- **prior** – A tuple as obtained from `petab.parameter.get_priors_from_df`
- **n_starts** – Number of samples

Returns Array with sampled values

```
petab.sampling.sample_parameter_startpoints (parameter_df: pandas.core.frame.DataFrame, n_starts: int = 100, seed: int = None) → numpy.array
```

Create numpy.array with starting points for an optimization

Parameters

- **parameter_df** – PETA parameter DataFrame
- **n_starts** – Number of points to be sampled
- **seed** – Random number generator seed (see numpy.random.seed)

Returns Array of sampled starting points with dimensions n_startpoints x n_optimization_parameters

11.12 petab.sbml

Functions for interacting with SBML models

Functions

<code>add_global_parameter(sbml_model, ...)</code>	Add new global parameter to SBML model
<code>add_model_output(sbml_model, observable_id, ...)</code>	Add PETA-style output to model
<code>add_model_output_sigma(sbml_model, ...)</code>	Add PETA-style sigma for the given observable id
<code>add_model_output_with_sigma(sbml_model, ...)</code>	Add PETA-style output and corresponding sigma with single (newly created) parameter
<code>assignment_rules_to_dict(sbml_model[, ...])</code>	Turn assignment rules into dictionary.
<code>create_assignment_rule(sbml_model, ...)</code>	Create SBML AssignmentRule
<code>get_model_parameters(sbml_model[, with_values])</code>	Return SBML model parameters which are not AssignmentRule targets for observables or sigmas
<code>get_observables(sbml_model, remove)</code>	Get observables defined in SBML model according to PETA format.
<code>get_sigmas(sbml_model, remove)</code>	Get sigmas defined in SBML model according to PETA format.
<code>globalize_parameters(sbml_model, ...)</code>	Turn all local parameters into global parameters with the same properties
<code>is_sbml_consistent(sbml_document, check_units)</code>	Check for SBML validity / consistency
<code>log_sbml_errors(sbml_document[, ...])</code>	Log libsbml errors
<code>sbml_parameter_is_observable(sbml_parameter)</code>	Returns whether the libsbml.Parameter sbml_parameter matches the defined observable format.
<code>sbml_parameter_is_sigma(sbml_parameter)</code>	Returns whether the libsbml.Parameter sbml_parameter matches the defined sigma format.
<code>write_sbml(sbml_doc, filename)</code>	Write PETA visualization table

```
petab.sbml.add_global_parameter(sbml_model: libsbml.Model, parameter_id: str, parameter_name: str = None, constant: bool = False, units: str = 'dimensionless', value: float = 0.0) → libsbml.Parameter
```

Add new global parameter to SBML model

Parameters

- **sbml_model** – SBML model
- **parameter_id** – ID of the new parameter
- **parameter_name** – Name of the new parameter
- **constant** – Is parameter constant?
- **units** – SBML unit ID
- **value** – parameter value

Returns The created parameter

```
petab.sbml.add_model_output(sbml_model: libsbml.Model, observable_id: str, formula: str, observable_name: str = None) → None
```

Add PETab-style output to model

We expect that all formula parameters are added to the model elsewhere.

Parameters

- **sbml_model** – Model to add output to
- **formula** – Formula string for model output
- **observable_id** – ID without “observable_” prefix
- **observable_name** – Any observable name

```
petab.sbml.add_model_output_sigma(sbml_model: libsbml.Model, observable_id: str, formula: str) → None
```

Add PETab-style sigma for the given observable id

We expect that all formula parameters are added to the model elsewhere.

Parameters

- **sbml_model** – Model to add to
- **observable_id** – Observable id for which to add sigma
- **formula** – Formula for sigma

```
petab.sbml.add_model_output_with_sigma(sbml_model: libsbml.Model, observable_id: str, observable_formula: str, observable_name: str = None) → None
```

Add PETab-style output and corresponding sigma with single (newly created) parameter

We expect that all formula parameters are added to the model elsewhere.

Parameters

- **sbml_model** – Model to add output to
- **observable_formula** – Formula string for model output
- **observable_id** – ID without “observable_” prefix
- **observable_name** – Any name

```
petab.sbml.assignment_rules_to_dict(sbml_model: libsbml.Model, filter_function=<function
<lambda>>, remove: bool = False) → Dict[str, Dict[str,
Any]]
```

Turn assignment rules into dictionary.

Parameters

- **sbml_model** – a sbml model instance.
- **filter_function** – callback function taking assignment variable as input and returning True/False to indicate if the respective rule should be turned into an observable.
- **remove** – Remove the all matching assignment rules from the model

Returns

```
{
    assigneeId:
    {
        'name': assigneeName,
        'formula': formulaString
    }
}
```

```
petab.sbml.create_assignment_rule(sbml_model: libsbml.Model, assignee_id: str, formula: str,
                                rule_id: str = None, rule_name: str = None) → libsbml.AssignmentRule
```

Create SBML AssignmentRule

Parameters

- **sbml_model** – Model to add output to
- **assignee_id** – Target of assignment
- **formula** – Formula string for model output
- **rule_id** – SBML id for created rule
- **rule_name** – SBML name for created rule

Returns The created AssignmentRule

```
petab.sbml.get_model_parameters(sbml_model: libsbml.Model, with_values=False) →
                                Union[List[str], Dict[str, float]]
```

Return SBML model parameters which are not AssignmentRule targets for observables or sigmas

Parameters

- **sbml_model** – SBML model
- **with_values** – If false, returns list of SBML model parameter IDs which
- **not AssignmentRule targets for observables or sigmas. If true, (are) –**
- **a dictionary with those parameter IDs as keys and parameter (returns) –**
- **from the SBML model as values. (values) –**

```
petab.sbml.get_observables(sbml_model: libsbml.Model, remove: bool = False) → dict
```

Get observables defined in SBML model according to PÉtab format.

Returns Dictionary of observable definitions. See *assignment_rules_to_dict* for details.

`petab.sbml.get_sigmas` (*sbml_model*: *libsbml.Model*, *remove*: *bool = False*) → dict
 Get sigmas defined in SBML model according to PTEtab format.

Returns

Dictionary of sigma definitions.

Keys are observable IDs, for values see *assignment_rules_to_dict* for details.

`petab.sbml.globalize_parameters` (*sbml_model*: *libsbml.Model*, *prepend_reaction_id*: *bool = False*) → None

Turn all local parameters into global parameters with the same properties

Local parameters are currently ignored by other PTEtab functions. Use this function to convert them to global parameters. There may exist local parameters with identical IDs within different kinetic laws. This is not checked here. If in doubt that local parameter IDs are unique, enable *prepend_reaction_id* to create global parameters named `{reaction_id}_{local_parameter_id}`.

Parameters

- **sbml_model** – The SBML model to operate on
- **prepend_reaction_id** – Prepend reaction id of local parameter when creating global parameters

`petab.sbml.is_sbml_consistent` (*sbml_document*: *libsbml.SBMLDocument*, *check_units*: *bool = False*) → bool

Check for SBML validity / consistency

Parameters

- **sbml_document** – SBML document to check
- **check_units** – Also check for unit-related issues

Returns False if problems were detected, otherwise True

`petab.sbml.log_sbml_errors` (*sbml_document*: *libsbml.SBMLDocument*, *minimum_severity*=1) → None

Log libsbml errors

Parameters

- **sbml_document** – SBML document to check
- **minimum_severity** – Minimum severity level to report (see libsbml)

`petab.sbml.sbml_parameter_is_observable` (*sbml_parameter*: *libsbml.Parameter*) → bool
 Returns whether the *libsbml.Parameter* *sbml_parameter* matches the defined observable format.

`petab.sbml.sbml_parameter_is_sigma` (*sbml_parameter*: *libsbml.Parameter*) → bool
 Returns whether the *libsbml.Parameter* *sbml_parameter* matches the defined sigma format.

`petab.sbml.write_sbml` (*sbml_doc*: *libsbml.SBMLDocument*, *filename*: *str*) → None
 Write PTEtab visualization table

Parameters

- **sbml_doc** – SBML document containing the SBML model
- **filename** – Destination file name

11.13 petab.yaml

Code regarding the PTEtab YAML config files

Functions

add_constructor	
add_implicit_resolver	
add_multi_constructor	
add_multi_representer	
add_path_resolver	
add_representer	
compose	
compose_all	
dump	
dump_all	
emit	
full_load	
full_load_all	
load	
load_all	
load_warning	
parse	
safe_dump	
safe_dump_all	
safe_load	
safe_load_all	
scan	
serialize	
serialize_all	
unsafe_load	
unsafe_load_all	
warnings	Python part of the warnings subsystem.

Classes

YAMLObject
YAMLObjectMetaclass

Exceptions

YAMLLoadWarning

`petab.yaml.assert_single_condition_and_sbml_file` (*problem_config*: *Dict[KT, VT]*) → *None*

Check that there is only a single condition file and a single SBML file specified.

Parameters *problem_config* – Dictionary as defined in the YAML schema inside the *problems* list.

Raises `NotImplementedError` – If multiple condition or SBML files specified.

`petab.yaml.is_composite_problem` (*yaml_config*: *Union[Dict[KT, VT], str]*) → *bool*

Does this YAML file comprise multiple models?

Parameters *yaml_config* – PEPetab configuration as dictionary or YAML file name

`petab.yaml.load_yaml(yaml_config: Union[Dict[KT, VT], str]) → Dict[KT, VT]`
 Load YAML

Convenience function to allow for providing YAML inputs either as filename or as dictionary.

Parameters `yaml_config` – PETab YAML config as filename or dict.

Returns The unmodified dictionary if `yaml_config` was dictionary. Otherwise the parsed the YAML file.

`petab.yaml.validate(yaml_config: Union[Dict[KT, VT], str], path_prefix: Optional[str] = None)`
 Validate syntax and semantics of PETab config YAML

Parameters

- **yaml_config** – PETab YAML config as filename or dict.
- **path_prefix** – Base location for relative paths. Defaults to location of YAML file if a filename was provided for `yaml_config` or the current working directory.

`petab.yaml.validate_yaml_semantics(yaml_config: Union[Dict[KT, VT], str], path_prefix: Optional[str] = None)`
 Validate PETab YAML file semantics

Check for existence of files. Assumes valid syntax.

Version number and contents of referenced files are not yet checked.

Parameters

- **yaml_config** – PETab YAML config as filename or dict.
- **path_prefix** – Base location for relative paths. Defaults to location of YAML file if a filename was provided for `yaml_config` or the current working directory.

Raises `AssertionError` – in case of problems

`petab.yaml.validate_yaml_syntax(yaml_config: Union[Dict[KT, VT], str], schema: Union[None, Dict[KT, VT], str] = None)`
 Validate PETab YAML file syntax

Parameters

- **yaml_config** – PETab YAML file to validate, as file name or dictionary
- **schema** – Custom schema for validation

Raises see `jsonschema.validate`

`petab.yaml.write_yaml(yaml_config: Dict[str, Any], filename: str) → None`
 Write PETab YAML file

Parameters

- **yaml_config** – Data to write
- **filename** – File to create

11.14 petab.visualize.data_overview

Functions for creating an overview report of a PETab problem

Functions

<code>create_report(problem, model_name)</code>	Create an HTML overview data / model overview report
<code>get_data_per_observable(measurement_df)</code>	Get table with number of data points per observable and condition
<code>main()</code>	Data overview generation with example data from the repository for testing

`petab.visualize.data_overview.create_report` (*problem:* `petab.problem.Problem`,
model_name: `str`) → `None`
Create an HTML overview data / model overview report

Parameters

- **problem** – PETab problem
- **model_name** – Name of the model, used for file name for report

`petab.visualize.data_overview.get_data_per_observable` (*measurement_df:* `pandas.core.frame.DataFrame`)
→ `pandas.core.frame.DataFrame`
Get table with number of data points per observable and condition

Parameters **measurement_df** – PETab measurement data frame

`petab.visualize.data_overview.main()`
Data overview generation with example data from the repository for testing

11.15 petab.visualize.helper_functions

This file should contain the functions, which PETab internally needs for plotting, but which are not meant to be used by non-developers and should hence not be directly visible/usable when using `import petab.visualize`.

Functions

<code>check_ex_exp_columns(exp_data, ...)</code>	Check the columns in measurement file, if non-mandatory columns does not exist, create default columns
<code>check_ex_visu_columns(vis_spec, ...)</code>	Check the columns in Visu_Spec file, if non-mandatory columns does not exist, create default columns
<code>check_vis_spec_consistency(exp_data, ...)</code>	Helper function for plotting data and simulations, which check the visualization setting, if no visualization specification file is provided.
<code>create_dataset_id_list(simcond_id_list, ...)</code>	Create dataset id list
<code>create_figure(uni_plot_ids, plots_to_file)</code>	Helper function for plotting data and simulations, open figure and axes
<code>get_data_to_plot(plot_spec, m_data, ...)</code>	group the data, which should be plotted and return it as dataframe.
<code>get_default_vis_specs(exp_data, ...)</code>	Helper function for plotting data and simulations, which creates a default visualization table.

Continued on next page

Table 17 – continued from previous page

<code>handle_dataset_plot(plot_spec, ax, exp_data, ...)</code>	Handle dataset plot
<code>import_from_files(data_file_path, ...)</code>	Helper function for plotting data and simulations, which imports data from PEPetab files.
<code>matches_plot_spec(df, col_id, x_value, str, ...)</code>	constructs an index for subsetting of the dataframe according to what is specified in plot_spec.

```
petab.visualize.helper_functions.check_exp_exp_columns(exp_data:      pandas.core.frame.DataFrame,
                                                       dataset_id_list: List[List[str]],
                                                       sim_cond_id_list: List[List[str]],
                                                       sim_cond_num_list: List[List[int]],
                                                       observable_id_list: List[List[str]],
                                                       observable_num_list: List[List[int]],
                                                       exp_conditions: pandas.core.frame.DataFrame)
→ Tuple[pandas.core.frame.DataFrame, List[List[str]], Dict[KT, VT]]
```

Check the columns in measurement file, if non-mandatory columns does not exist, create default columns

```
petab.visualize.helper_functions.check_exp_visu_columns(vis_spec:      pandas.core.frame.DataFrame,
                                                         dataset_id_list: List[List[str]],
                                                         legend_dict: Dict[KT, VT]) → pandas.core.frame.DataFrame
```

Check the columns in Visu_Spec file, if non-mandatory columns does not exist, create default columns

```
petab.visualize.helper_functions.check_vis_spec_consistency(exp_data:      pandas.core.frame.DataFrame,
                                                             dataset_id_list: Optional[List[List[str]]]
                                                             = None,
                                                             sim_cond_id_list: Optional[List[List[str]]]
                                                             = None,
                                                             sim_cond_num_list: Optional[List[List[int]]]
                                                             = None,
                                                             observable_id_list: Optional[List[List[str]]]
                                                             = None,
                                                             observable_num_list: Optional[List[List[int]]]
                                                             = None) → str
```

Helper function for plotting data and simulations, which check the visualization setting, if no visualization specification file is provided.

For documentation, see main function `plot_data_and_simulation()`

```
petab.visualize.helper_functions.create_dataset_id_list (simcond_id_list:
                                                         List[List[str]],      sim-
                                                         cond_num_list:
                                                         List[List[int]],      ob-
                                                         servable_id_list:
                                                         List[List[str]],      ob-
                                                         servable_num_list:
                                                         List[List[int]],
                                                         exp_data:             pan-
                                                         das.core.frame.DataFrame,
                                                         exp_conditions:       pan-
                                                         das.core.frame.DataFrame,
                                                         group_by: str) → Tu-
                                                         ple[pandas.core.frame.DataFrame,
                                                         List[List[str]],      Dict[KT,
                                                         VT]]
```

Create dataset id list

```
petab.visualize.helper_functions.create_figure (uni_plot_ids:      numpy.ndarray,
                                                plots_to_file: bool) → Tu-
                                                ple[matplotlib.figure.Figure,
                                                Union[Dict[str,          mat-
                                                plotlib.axes._subplots.AxesSubplot],
                                                np.ndarray[plt.Subplot]]]
```

Helper function for plotting data and simulations, open figure and axes

Parameters

- **uni_plot_ids** – Array with unique plot indices
- **plots_to_file** – Indicator if plots are saved to file

Returns

- **fig** (*Figure object of the created plot.*)
- **ax** (*Axis object of the created plot.*)

```
petab.visualize.helper_functions.get_data_to_plot (plot_spec:      pan-
                                                  das.core.series.Series,      m_data:
                                                  pandas.core.frame.DataFrame,
                                                  simulation_data:            pan-
                                                  das.core.frame.DataFrame,
                                                  condition_ids:             numpy.ndarray,
                                                  col_id: str, simulation_field:
                                                  str = 'simulation') → pan-
                                                  das.core.frame.DataFrame
```

group the data, which should be plotted and return it as dataframe.

Parameters

- **plot_spec** – information about contains defined data format (visualization file)
- **m_data** – contains defined data format (measurement file)
- **simulation_data** – contains defined data format (simulation file)
- **condition_ids** – contains all unique condition IDs which should be plotted in one figure (can be found in measurementData file, column simulationConditionId)

- **col_id** – the name of the column in visualization file, whose entries should be unique (depends on condition in column independentVariableName)
- **simulation_field** – Column name in `simulation_data` that contains the actual simulation result.

Returns contains the data which should be plotted (Mean and Std)

Return type `data_to_plot`

```
petab.visualize.helper_functions.get_default_vis_specs (exp_data:      pandas.core.frame.DataFrame,
                                                         exp_conditions:      pandas.core.frame.DataFrame,
                                                         dataset_id_list:      Optional[List[List[str]]] =
                                                         None,      sim_cond_id_list:
                                                         Optional[List[List[str]]] =
                                                         None,      sim_cond_num_list:
                                                         Optional[List[List[int]]] =
                                                         None,      observable_id_list:
                                                         Optional[List[List[str]]] =
                                                         None,      observable_num_list:
                                                         Optional[List[List[int]]]
                                                         = None,      plotted_noise:
                                                         Optional[str] =
                                                         'MeanAndSD') → Tuple[
                                                         pandas.core.frame.DataFrame,
                                                         pandas.core.frame.DataFrame]
```

Helper function for plotting data and simulations, which creates a default visualization table.

For documentation, see main function `plot_data_and_simulation()`

```
petab.visualize.helper_functions.handle_dataset_plot (plot_spec:      pandas.core.series.Series,      ax:
                                                         matplotlib.axes._axes.Axes,
                                                         exp_data:      pandas.core.frame.DataFrame,
                                                         exp_conditions:      pandas.core.frame.DataFrame,
                                                         sim_data:      pandas.core.frame.DataFrame)
```

Handle dataset plot

```
petab.visualize.helper_functions.import_from_files (data_file_path:      str,      con-
                                                    dition_file_path:      str,      vi-
                                                    sualization_file_path:      str,
                                                    simulation_file_path:      str,
                                                    dataset_id_list:      List[List[str]],
                                                    sim_cond_id_list:      List[List[str]],
                                                    sim_cond_num_list:
List[List[int]], observable_id_list:
List[List[str]], observ-
able_num_list:      List[List[int]],
plotted_noise:      str) → Tu-
ple[pandas.core.frame.DataFrame,
pandas.core.frame.DataFrame,
pandas.core.frame.DataFrame,
pandas.core.frame.DataFrame]
```

Helper function for plotting data and simulations, which imports data from PETab files.

For documentation, see main function `plot_data_and_simulation()`

```
petab.visualize.helper_functions.matches_plot_spec (df:      pan-
                                                    das.core.frame.DataFrame,
                                                    col_id: str, x_value: Union[float,
str],      plot_spec:      pan-
                                                    das.core.series.Series) → pan-
                                                    das.core.series.Series
```

constructs an index for subsetting of the dataframe according to what is specified in `plot_spec`.

Parameters

- **df** – pandas data frame to subset, can be from measurement file or simulation file
- **col_id** – name of the column that will be used for indexing in x variable
- **x_value** – subsetting x value
- **plot_spec** – visualization spec from the visualization file

Returns boolean series that can be used for subsetting of the passed dataframe

Return type index

11.16 petab.visualize.plot_data_and_simulation

```
petab.visualize.plot_data_and_simulation(exp_data: Union[str, pandas.core.frame.DataFrame], exp_conditions: Union[str, pandas.core.frame.DataFrame], vis_spec: Union[str, pandas.core.frame.DataFrame, None] = "", sim_data: Union[str, pandas.core.frame.DataFrame, None] = None, dataset_id_list: Optional[List[List[str]]] = None, sim_cond_id_list: Optional[List[List[str]]] = None, sim_cond_num_list: Optional[List[List[int]]] = None, observable_id_list: Optional[List[List[str]]] = None, observable_num_list: Optional[List[List[int]]] = None, plotted_noise: Optional[str] = 'MeanAndSD', subplot_file_path: str = "") → Union[Dict[str, matplotlib.axes._subplots.AxesSubplot], np.ndarray[plt.Subplot], None]
```

Main function for plotting data and simulations.

What exactly should be plotted is specified in a visualizationSpecification.tsv file.

Also, the data, simulations and conditions have to be defined in a specific format (see “doc/documentation_data_format.md”).

Parameters

- **exp_data** – measurement DataFrame in the PEOtab format or path to the data file.
- **exp_conditions** – condition DataFrame in the PEOtab format or path to the condition file.
- **vis_spec** (*str or pandas.DataFrame (optional)*) – Visualization specification DataFrame in the PEOtab format or path to visualization file.
- **sim_data** – simulation DataFrame in the PEOtab format or path to the simulation output data file.
- **dataset_id_list** – A list of lists. Each sublist corresponds to a plot, each subplot contains the datasetIds for this plot. Only to be used if no visualization file was available.
- **sim_cond_id_list** – A list of lists. Each sublist corresponds to a plot, each subplot contains the simulationConditionIds for this plot. Only to be used if no visualization file was available.
- **sim_cond_num_list** – A list of lists. Each sublist corresponds to a plot, each subplot contains the numbers corresponding to the simulationConditionIds for this plot. Only to be used if no visualization file was available.
- **observable_id_list** – A list of lists. Each sublist corresponds to a plot, each subplot contains the observableIds for this plot. Only to be used if no visualization file was available.
- **observable_num_list** – A list of lists. Each sublist corresponds to a plot, each subplot contains the numbers corresponding to the observableIds for this plot. Only to be used if no visualization file was available.

- **plotted_noise** – String indicating how noise should be visualized: ['MeanAndSD' (default), 'MeanAndSEM', 'replicate', 'provided']
- **subplot_file_path** – String which is taken as file path to which single subplots are saved. PlotIDs will be taken as file names.

Returns

- **ax** (*Axis object of the created plot.*)
- **None** (*In case subplots are save to file*)

11.17 petab.visualize.plotting_config

Plotting config

Functions

<code>plot_lowlevel(plot_spec, ax, conditions, ms, ...)</code>	plotting routine / preparations: set properties of figure and plot the data with given specifications (lineplot with errorbars, or barplot)
<code>square_plot_equal_ranges(ax, lim, Tuple, ...)</code>	Square plot with equal range for scatter plots

`petab.visualize.plotting_config.plot_lowlevel` (*plot_spec: pandas.core.series.Series, ax: matplotlib.pyplot.Axes, conditions: pandas.core.series.Series, ms: pandas.core.frame.DataFrame, plot_sim: bool*) → *matplotlib.pyplot.Axes*
 plotting routine / preparations: set properties of figure and plot the data with given specifications (lineplot with errorbars, or barplot)

Parameters

- **plot_spec** – contains defined data format (visualization file)
- **ax** – axes to which to plot
- **conditions** – Values on x-axis
- **ms** – contains measurement data which should be plotted
- **plot_sim** – tells whether or not simulated data should be plotted as well

`petab.visualize.plotting_config.square_plot_equal_ranges` (*ax: matplotlib.pyplot.Axes, lim: Union[List[T], Tuple, None] = None*) → *matplotlib.pyplot.Axes*
 Square plot with equal range for scatter plots

12.1 0.1 series

12.1.1 0.1.5

Library:

- New create empty observable function (issue 386) (#387)
- Deprecate `petab.sbml.globalize_parameters` (#381)
- Fix computing \log_{10} likelihood (#380)
- Documentation update and typehints for visualization (#372)
- Ordered result of `petab.get_output_parameters`
- Fix missing argument to `parameters.create_parameter_df`

Documentation:

- Add overview of supported PEPetab feature in toolboxes
- Add contribution guide
- Fix optional values in documentation (#378)

12.1.2 0.1.4

Library:

- Fixes / updates in functions for computing llh and chi^2
- Allow and require output parameters defined in observable table to be defined in parameter table
- Fix `merge_preeq_and_sim_pars_condition` which incorrectly assumed lists instead of dicts
- Update parameter mapping to deal with species and compartments in condition table

- Removed `petab.migrations.sbml_observables_to_table`

For converting older PEtab files to observable table format, use one of the previous releases

- Visualization:
 - Fix various issues with `get_data_to_plot`
 - Fixed various issues with expected presence of optional columns

12.1.3 0.1.3

File format:

- Updated documentation
- Observables table in YAML file now mandatory in schema (was implicitly mandatory before, as observable table was required already)

Library:

- petablint:
 - Fix: allow specifying observables file via CLI (Closes #302)
 - Fix: nominalValue is optional unless estimated!=1 anywhere (Fixes #303)
 - Fix: handle undefined observables more gracefully (Closes #300) (#351)
- Parameter mapping:
 - Fix / refactor parameter mapping (breaking change) (#344) (now performing parameter value and scale mapping together)
 - check optional measurement cols in mapping (#350)
- allow calculating llhs (#349), chi2 values (#348) and residuals (#345)
- Visualization
 - Basic Scatterplots & lot of bar plot fixes (#270)
 - Fix incorrect length of bool `bool_preequ` when subsetting with `ind_meas` (Closes #322)
- make libcombine optional (#338)

12.1.4 0.1.2

Library:

- Extensions and fixes for the visualization functions (#255, #262)
- Allow to extract fixed/free and scaled/non-scaled parameters (#256, #268, #273)
- Various fixes (esp. #264)
- Add function to get observable ids (#269)
- Improve documentation (esp. #289)
- Set default column for simulation results to 'simulation'
- Add support for COMBINE archives (#271)
- Fix sbml observables to table

- Improve prior and dataframe tests (#285, #286, #297)
- Add function to get parameter table with all default values (#288)
- Move tests to github actions (#281)
- Check for valid identifiers
- Fix handling of empty values in dataframes
- Allow to get numeric values in parameter mappings in scaled form (#308)

12.1.5 0.1.1

Library:

- Fix parameter mapping: include output parameters not present in SBML model
- Fix missing `petab/petab_schema.yaml` in source distribution
- Let `get_placeholders` return an (ordered) list of placeholders
- Deprecate `petab.problem.from_folder` and related functions (obsolete after introducing more flexible YAML files for grouping tables and models)

12.1.6 0.1.0

Data format:

- Introduce observables table instead of SBML assignment rules for defining observation model (#244) (moves `observableTransformation` and `noiseModel` from the measurement table to the observables table)
- Allow initial concentrations / sizes in condition table (#238)
- Fixes and clarifications in the format documentation
- Changes in prior columns of the parameter table (#222)
- Introduced separate version number of file format, this release being version 1

Library:

- Adaptations to new file formats
- Various bugfixes and clean-up, especially in visualization and validator
- Parameter mapping changed to include all model parameters and not only those differing from the ones defined inside the SBML model
- Introduced constants for all field names and string options, replacing most string literals in the code (#228)
- Added unit tests and additional format validation steps
- Optional parallelization of parameter mapping (#205)
- Extended documentation (in-source and example Jupyter notebooks)

12.1.7 0.0.2

Bugfix release

- Fix `petablint` error

- Fix minor issues in `petab.visualize`

12.1.8 0.0.1

Data format:

- Update format and documentation with respect to data and parameter scales (#169)
- Define YAML schema for grouping PEPtab files, also allowing for more complex combinations of files (#183)

Library:

- Refactor library. Reorganize `petab.core` functions.
- Fix visualization w/o condition names #142
- Extend validator
- Removed deprecated functions `petab.Problem.get_constant_parameters` and `petab.sbml.constant_species_to_parameters`
- Minor fixes and extensions

12.2 0.0 series

12.2.1 0.0.0a17

Data format: *No changes*

Library:

- Extended visualization support
- Add helper function and test case to deal with timepoint-specific parameters `flatten_timepoint_specific_output_overrides` (#128) (Closes #125)
- Fix `get_noise_distributions`: so far we got ‘normal’ everywhere due to wrong grouping (#147)
- Fix `create_parameter_df`: Exclude rule targets (#149)
- Verify condition table column names occur as model parameters (Closes #150) (#151)
- More informative error messages in case of wrongly set observable and noise parameters (Closes #118) (#155)
- Update doc for copasi import and github installation (#158)
- Extend validator to check if all required parameters are present in parameter table (Closes #43) (#159)
- Setup documentation for RTD (#161)
- Handle None in `petab.core.split_parameter_replacement_list` (Closes #121)
- Fix(lint) correct handling of optional columns. Check before access.
- Remove obsolete `generate_experiment_id.py` (Closes #111) #166

12.2.2 0.0.0a16 and earlier

See git history

CHAPTER 13

License

MIT License

Copyright (c) 2018 Data-driven Computational Modelling

Permission **is** hereby granted, free of charge, to **any** person obtaining a copy of this software **and** associated documentation files (the "**Software**"), to deal **in** the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, **and/or** sell copies of the Software, **and** to permit persons to whom the Software **is** furnished to do so, subject to the following conditions:

The above copyright notice **and** this permission notice shall be included **in all** copies **or** substantial portions of the Software.

THE SOFTWARE IS PROVIDED "**AS IS**", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

CHAPTER 14

PEtab logo license

The PEOab logo is free for use under the CC0 license.



PEtab

The following examples should help to get a better idea of how to use the PETab library.

15.1 Using petablnt

petablnt is a tool to validate a model against the PETab standard. When you have installed PETab, you can simply call it from the command line. It takes the following arguments:

```
[1]: !petablnt -h

usage: petablnt [-h] [-v] [-s SBML_FILE_NAME] [-m MEASUREMENT_FILE_NAME]
               [-c CONDITION_FILE_NAME] [-p PARAMETER_FILE_NAME]
               [-y YAML_FILE_NAME | -n MODEL_NAME] [-d DIRECTORY]

Check if a set of files adheres to the PETab format.

optional arguments:
  -h, --help                show this help message and exit
  -v, --verbose             More verbose output
  -s SBML_FILE_NAME, --sbml SBML_FILE_NAME
                           SBML model filename
  -m MEASUREMENT_FILE_NAME, --measurements MEASUREMENT_FILE_NAME
                           Measurement table
  -c CONDITION_FILE_NAME, --conditions CONDITION_FILE_NAME
                           Conditions table
  -p PARAMETER_FILE_NAME, --parameters PARAMETER_FILE_NAME
                           Parameter table
  -y YAML_FILE_NAME, --yaml YAML_FILE_NAME
                           PETab YAML problem filename
  -n MODEL_NAME, --model-name MODEL_NAME
                           Model name where all files are in the working
                           directory and follow PETab naming convention.
                           Specifying -[smcp] will override defaults
  -d DIRECTORY, --directory DIRECTORY
```

Let's look at an example: In the `example_Fujita` folder, we have a PEtab configuration file `Fujita.yaml` telling which files belong to the Fujita model:

```
[2]: !cat example_Fujita/Fujita.yaml

parameter_file: Fujita_parameters.tsv
petab_version: 0.0.0a17
problems:
- condition_files:
  - Fujita_experimentalCondition.tsv
  measurement_files:
  - Fujita_measurementData.tsv
  sbml_files:
  - Fujita_model.xml
```

To verify everything is ok, we can just call:

```
[3]: !petablint -y example_Fujita/Fujita.yaml
```

If there were some inconsistency or error, we would see that here. `petablint` can be called in different ways. You can e.g. also pass SBML, measurement, condition, and parameter file directly, or, if the files follow PEtab naming conventions, you can just pass the model name.

15.2 Visualization of data and simulations

In this notebook, we illustrate the visualization functions of `petab`.


```
[1]: from petab.visualize import plot_data_and_simulation
import matplotlib.pyplot as plt
```

```
[2]: folder = "example_Isensee/"

data_file_path = folder + "Isensee_measurementData.tsv"
condition_file_path = folder + "Isensee_experimentalCondition.tsv"
visualization_file_path = folder + "Isensee_visualizationSpecification.tsv"
simulation_file_path = folder + "Isensee_simulationData.tsv"


# function to call, to plot data and simulations
ax = plot_data_and_simulation(data_file_path,
                             condition_file_path,
                             visualization_file_path,
                             simulation_file_path)

plt.show()
```



Now, we want to call the plotting routines without using the simulated data, only the visualization specification file.

```
[3]: ax_without_sim = plot_data_and_simulation(
    data_file_path,
    condition_file_path,
    visualization_file_path)
plt.show()
```




We can also call the plotting routine without the visualization specification file, but by passing a list of lists as `dataset_id_list`. Each sublist corresponds to a plot, and contains the datasetIds which should be plotted. In this simply structured plotting routine, the independent variable will always be time.

```
[4]: ax_without_sim = plot_data_and_simulation(
```

(continues on next page)

(continued from previous page)




Let's look more closely at the plotting routines, if no visualization specification file is provided. If such a file is missing, PETA needs to know how to group the data points. For this, five options can be used: * dataset_id_list * sim_cond_id_list * sim_cond_num_list * observable_id_list * observable_num_list

Each of them is a list of lists. Again, each sublist is a plot and its content are either simulation condition IDs or observable IDs (or their corresponding number when being enumerated) or the dataset IDs.


We want to illustrate this functionality by using a simpler example, a model published in 2010 by Fujita et al.

```
[5]: data_file_path = "example_Fujita/Fujita_measurementData.tsv"
condition_file_path = "example_Fujita/Fujita_experimentalCondition.tsv"


# Plot 4 axes objects, plotting
# - in the first window all observables of the 1st, 2nd, and 3rd simulation condition
# - in the second window all observables of the 1st, 3rd, and 4th simulation condition
# - in the third window all observables of the 1st, 4th, and 5th simulation condition
# - in the fourth window all observables of the 1st, 5th, and 6th simulation condition
plot_data_and_simulation(data_file_path, condition_file_path,
                        sim_cond_num_list = [[0, 1, 2], [0, 2, 3], [0, 3, 4], [0, 4, 5]])
plt.show()
```



```
[6]: # Plot 4 axes objects, plotting
# - in the first window all observables of the simulation condition 'modell_data1'
# - in the second window all observables of the simulation conditions 'modell_data2',
#    ↪ 'modell_data3'
# - in the third window all observables of the simulation conditions 'modell_data4',
#    ↪ 'modell_data5'
# - in the fourth window all observables of the simulation condition 'modell_data6'
plot_data_and_simulation(
    data_file_path, condition_file_path,
    sim_cond_id_list = [['modell_data1'], ['modell_data2', 'modell_data3'],
                       ['modell_data4', 'modell_data5'], ['modell_data6']])
plt.show()
```




```
[7]: # Plot 5 axes objects, plotting
# - in the first window the 1st observable for all simulation conditions
# - in the second window the 2nd observable for all simulation conditions
# - in the third window the 3rd observable for all simulation conditions
# - in the fourth window the 1st and 3rd observable for all simulation conditions
# - in the fifth window the 2nd and 3rd observable for all simulation conditions
plot_data_and_simulation(
    data_file_path, condition_file_path,
    observable_num_list = [[0], [1], [2], [0, 2], [1, 2]])
plt.show()
```




```
[8]: # Plot 3 axes objects, plotting
# - in the first window the observable 'pS6_tot' for all simulation conditions
# - in the second window the observable 'pEGFR_tot' for all simulation conditions
# - in the third window the observable 'pAkt_tot' for all simulation conditions

plot_data_and_simulation(
    data_file_path, condition_file_path,
    observable_id_list = [['pS6_tot'], ['pEGFR_tot'], ['pAkt_tot']])
plt.show()
```

```
[9]: # Plot 2 axes objects, plotting
# - in the first window the observable 'pS6_tot' for all simulation conditions
# - in the second window the observable 'pEGFR_tot' for all simulation conditions
# - in the third window the observable 'pAkt_tot' for all simulation conditions
# while using the noise values which are saved in the PTEtab files
```

```
plot_data_and_simulation(
    data_file_path, condition_file_path,
    observable_id_list = [['pS6_tot'], ['pEGFR_tot']],
    plotted_noise='provided')
plt.show()
```



CHAPTER 16

Indices and tables

- `genindex`
- `modindex`
- `search`

p

- `petab`, [23](#)
- `petab.C`, [27](#)
- `petab.composite_problem`, [24](#)
- `petab.conditions`, [27](#)
- `petab.core`, [24](#)
- `petab.lint`, [28](#)
- `petab.measurements`, [33](#)
- `petab.parameter_mapping`, [35](#)
- `petab.parameters`, [41](#)
- `petab.problem`, [44](#)
- `petab.sampling`, [49](#)
- `petab.sbml`, [50](#)
- `petab.visualize.data_overview`, [55](#)
- `petab.visualize.helper_functions`, [56](#)
- `petab.visualize.plotting_config`, [62](#)
- `petab.yaml`, [53](#)

Symbols

`_apply_condition_parameters()` (in module *petab.parameter_mapping*), 36
`_apply_mask()` (*petab.problem.Problem* method), 45
`_apply_output_parameter_overrides()` (in module *petab.parameter_mapping*), 36
`_apply_overrides_for_observable()` (in module *petab.parameter_mapping*), 36
`_apply_parameter_table()` (in module *petab.parameter_mapping*), 36
`_check_df()` (in module *petab.lint*), 29
`_map_condition()` (in module *petab.parameter_mapping*), 37
`_map_condition_arg_packer()` (in module *petab.parameter_mapping*), 37
`_output_parameters_to_nan()` (in module *petab.parameter_mapping*), 37
`_perform_mapping_checks()` (in module *petab.parameter_mapping*), 37

A

`add_global_parameter()` (in module *petab.sbml*), 51
`add_model_output()` (in module *petab.sbml*), 51
`add_model_output_sigma()` (in module *petab.sbml*), 51
`add_model_output_with_sigma()` (in module *petab.sbml*), 51
`assert_all_parameters_present_in_parameter_df()` (in module *petab.lint*), 29
`assert_measured_observables_defined()` (in module *petab.lint*), 29
`assert_measurement_conditions_present_in_condition_table()` (in module *petab.lint*), 29
`assert_model_parameters_in_condition_or_parameter_table()` (in module *petab.lint*), 30
`assert_no_leading_trailing_whitespace()` (in module *petab.lint*), 30
`assert_noise_distributions_valid()` (in

module *petab.lint*), 30
`assert_overrides_match_parameter_count()` (in module *petab.measurements*), 34
`assert_parameter_bounds_are_numeric()` (in module *petab.lint*), 30
`assert_parameter_estimate_is_boolean()` (in module *petab.lint*), 30
`assert_parameter_id_is_string()` (in module *petab.lint*), 31
`assert_parameter_id_is_unique()` (in module *petab.lint*), 31
`assert_parameter_prior_parameters_are_valid()` (in module *petab.lint*), 31
`assert_parameter_prior_type_is_valid()` (in module *petab.lint*), 31
`assert_parameter_scale_is_valid()` (in module *petab.lint*), 31
`assert_single_condition_and_sbml_file()` (in module *petab.yaml*), 54
`assignment_rules_to_dict()` (in module *petab.sbml*), 51

C

`check_condition_df()` (in module *petab.lint*), 31
`check_ex_exp_columns()` (in module *petab.visualize.helper_functions*), 57
`check_ex_visu_columns()` (in module *petab.visualize.helper_functions*), 57
`check_ids()` (in module *petab.lint*), 31
`check_measurement_df()` (in module *petab.lint*), 31
`check_observable_df()` (in module *petab.lint*), 32
`check_parameter_bounds()` (in module *petab.lint*), 32
`check_parameter_df()` (in module *petab.lint*), 32
`check_vis_spec_consistency()` (in module *petab.visualize.helper_functions*), 57
`CompositeProblem` (class in module *petab.composite_problem*), 24
`concat_tables()` (in module *petab.core*), 25

[condition_df \(petab.problem.Problem attribute\), 45](#)
[condition_table_is_parameter_free\(\) \(in module petab.lint\), 32](#)
[create_assignment_rule\(\) \(in module petab.sbml\), 52](#)
[create_combine_archive\(\) \(in module petab.core\), 25](#)
[create_condition_df\(\) \(in module petab.conditions\), 27](#)
[create_dataset_id_list\(\) \(in module petab.visualize.helper_functions\), 58](#)
[create_figure\(\) \(in module petab.visualize.helper_functions\), 58](#)
[create_measurement_df\(\) \(in module petab.measurements\), 34](#)
[create_parameter_df\(\) \(in module petab.parameters\), 42](#)
[create_parameter_df\(\) \(petab.problem.Problem method\), 45](#)
[create_report\(\) \(in module petab.visualize.data_overview\), 56](#)

E

[ENV_NUM_THREADS \(in module petab\), 23](#)

F

[flatten_timepoint_specific_output_overrides\(\) \(in module petab.core\), 25](#)
[from_combine\(\) \(petab.problem.Problem static method\), 45](#)
[from_files\(\) \(petab.problem.Problem static method\), 46](#)
[from_folder\(\) \(petab.problem.Problem static method\), 46](#)
[from_yaml\(\) \(petab.composite_problem.CompositeProblem static method\), 24](#)
[from_yaml\(\) \(petab.problem.Problem static method\), 46](#)

G

[get_condition_df\(\) \(in module petab.conditions\), 27](#)
[get_data_per_observable\(\) \(in module petab.visualize.data_overview\), 56](#)
[get_data_to_plot\(\) \(in module petab.visualize.helper_functions\), 58](#)
[get_default_condition_file_name\(\) \(in module petab.problem\), 49](#)
[get_default_measurement_file_name\(\) \(in module petab.problem\), 49](#)
[get_default_parameter_file_name\(\) \(in module petab.problem\), 49](#)
[get_default_sbml_file_name\(\) \(in module petab.problem\), 49](#)

[get_default_vis_specs\(\) \(in module petab.visualize.helper_functions\), 59](#)
[get_lb\(\) \(petab.problem.Problem method\), 46](#)
[get_measurement_df\(\) \(in module petab.measurements\), 34](#)
[get_measurement_parameter_ids\(\) \(in module petab.measurements\), 34](#)
[get_model_parameters\(\) \(in module petab.sbml\), 52](#)
[get_model_parameters\(\) \(petab.problem.Problem method\), 46](#)
[get_noise_distributions\(\) \(in module petab.measurements\), 34](#)
[get_noise_distributions\(\) \(petab.problem.Problem method\), 47](#)
[get_notnull_columns\(\) \(in module petab.core\), 25](#)
[get_observable_id\(\) \(in module petab.core\), 25](#)
[get_observable_ids\(\) \(petab.problem.Problem method\), 47](#)
[get_observables\(\) \(in module petab.sbml\), 52](#)
[get_observables\(\) \(petab.problem.Problem method\), 47](#)
[get_optimization_parameter_scales\(\) \(petab.problem.Problem method\), 47](#)
[get_optimization_parameter_scaling\(\) \(in module petab.parameters\), 42](#)
[get_optimization_parameters\(\) \(in module petab.parameters\), 42](#)
[get_optimization_parameters\(\) \(petab.problem.Problem method\), 47](#)
[get_optimization_to_simulation_parameter_mapping\(\) \(in module petab.parameter_mapping\), 37](#)
[get_optimization_to_simulation_parameter_mapping\(\) \(petab.problem.Problem method\), 47](#)
[get_parameter_df\(\) \(in module petab.parameters\), 42](#)
[get_parameter_mapping_for_condition\(\) \(in module petab.parameter_mapping\), 39](#)
[get_parametric_overrides\(\) \(in module petab.conditions\), 27](#)
[get_priors_from_df\(\) \(in module petab.parameters\), 42](#)
[get_required_parameters_for_parameter_table\(\) \(in module petab.parameters\), 43](#)
[get_rows_for_condition\(\) \(in module petab.measurements\), 34](#)
[get_sigmas\(\) \(in module petab.sbml\), 52](#)
[get_sigmas\(\) \(petab.problem.Problem method\), 47](#)
[get_simulation_conditions\(\) \(in module petab.measurements\), 34](#)
[get_simulation_conditions_from_measurement_df\(\) \(petab.problem.Problem method\), 47](#)
[get_simulation_df\(\) \(in module petab.core\), 26](#)

get_ub() (*petab.problem.Problem* method), 47
 get_valid_parameters_for_parameter_table()
 (in module *petab.parameters*), 43
 get_visualization_df() (in module *petab.core*),
 26
 get_x_ids() (*petab.problem.Problem* method), 47
 get_x_nominal() (*petab.problem.Problem* method),
 47
 globalize_parameters() (in module *petab.sbml*),
 53

H

handle_dataset_plot() (in module
 petab.visualize.helper_functions), 59
 handle_missing_overrides() (in module
 petab.parameter_mapping), 40

I

import_from_files() (in module
 petab.visualize.helper_functions), 59
 is_composite_problem() (in module *petab.yaml*),
 54
 is_empty() (in module *petab.core*), 26
 is_sbml_consistent() (in module *petab.sbml*), 53
 is_valid_identifier() (in module *petab.lint*), 32

L

lb (*petab.problem.Problem* attribute), 48
 lb_scaled (*petab.problem.Problem* attribute), 48
 lint_problem() (in module *petab.lint*), 32
 load_yaml() (in module *petab.yaml*), 54
 log_sbml_errors() (in module *petab.sbml*), 53

M

main() (in module *petab.visualize.data_overview*), 56
 map_scale() (in module *petab.parameters*), 43
 matches_plot_spec() (in module
 petab.visualize.helper_functions), 60
 measurement_df (*petab.problem.Problem* attribute),
 45
 measurement_table_has_observable_parameter_name()
 (in module *petab.lint*), 33
 measurement_table_has_timepoint_specific_mappings()
 (in module *petab.lint*), 33
 measurements_have_replicates() (in module
 petab.measurements), 35
 merge_preeq_and_sim_pars() (in module
 petab.parameter_mapping), 40
 merge_preeq_and_sim_pars_condition() (in
 module *petab.parameter_mapping*), 41

N

normalize_parameter_df() (in module
 petab.parameters), 43

O

observable_df (*petab.problem.Problem* attribute),
 45

P

parameter_df (*petab.composite_problem.CompositeProblem*
 attribute), 24
 parameter_df (*petab.problem.Problem* attribute), 45
 petab (module), 23
 petab.C (module), 27
 petab.composite_problem (module), 24
 petab.conditions (module), 27
 petab.core (module), 24
 petab.lint (module), 28
 petab.measurements (module), 33
 petab.parameter_mapping (module), 35
 petab.parameters (module), 41
 petab.problem (module), 44
 petab.sampling (module), 49
 petab.sbml (module), 50
 petab.visualize.data_overview (module), 55
 petab.visualize.helper_functions (mod-
 ule), 56
 petab.visualize.plotting_config (module),
 62
 petab.yaml (module), 53
 plot_data_and_simulation() (in module
 petab.visualize), 61
 plot_lowlevel() (in module
 petab.visualize.plotting_config), 62
 Problem (class in *petab.problem*), 45
 problems (*petab.composite_problem.CompositeProblem*
 attribute), 24

S

sample_from_prior() (in module *petab.sampling*),
 49
 sample_parameter_startpoints() (in module
 petab.sampling), 49
 sample_parameter_startpoints()
 (*petab.problem.Problem* method), 48
 sbml_document (*petab.problem.Problem* attribute),
 45
 sbml_model (*petab.problem.Problem* attribute), 45
 sbml_parameter_is_observable() (in module
 petab.sbml), 53
 sbml_parameter_is_sigma() (in module
 petab.sbml), 53
 sbml_reader (*petab.problem.Problem* attribute), 45
 scale() (in module *petab.parameters*), 44
 split_parameter_replacement_list() (in
 module *petab.measurements*), 35
 square_plot_equal_ranges() (in module
 petab.visualize.plotting_config), 62

T

`to_files()` (*petab.problem.Problem* method), 48
`to_float_if_float()` (in module *petab.core*), 26

U

`ub` (*petab.problem.Problem* attribute), 48
`ub_scaled` (*petab.problem.Problem* attribute), 48
`unique_preserve_order()` (in module *petab.core*), 26
`unscale()` (in module *petab.parameters*), 44

V

`validate()` (in module *petab.yaml*), 55
`validate_yaml_semantics()` (in module *petab.yaml*), 55
`validate_yaml_syntax()` (in module *petab.yaml*), 55
`visualization_df` (*petab.problem.Problem* attribute), 45

W

`write_condition_df()` (in module *petab.conditions*), 27
`write_measurement_df()` (in module *petab.measurements*), 35
`write_parameter_df()` (in module *petab.parameters*), 44
`write_sbml()` (in module *petab.sbml*), 53
`write_simulation_df()` (in module *petab.core*), 26
`write_visualization_df()` (in module *petab.core*), 26
`write_yaml()` (in module *petab.yaml*), 55

X

`x_fixed_ids` (*petab.problem.Problem* attribute), 48
`x_fixed_indices` (*petab.problem.Problem* attribute), 48
`x_free_ids` (*petab.problem.Problem* attribute), 48
`x_free_indices` (*petab.problem.Problem* attribute), 48
`x_ids` (*petab.problem.Problem* attribute), 49
`x_nominal` (*petab.problem.Problem* attribute), 49
`x_nominal_fixed` (*petab.problem.Problem* attribute), 49
`x_nominal_fixed_scaled` (*petab.problem.Problem* attribute), 49
`x_nominal_free` (*petab.problem.Problem* attribute), 49
`x_nominal_free_scaled` (*petab.problem.Problem* attribute), 49
`x_nominal_scaled` (*petab.problem.Problem* attribute), 49